


CITY OF MARYSVILLE AGENDA BILL

EXECUTIVE SUMMARY FOR ACTION

CITY COUNCIL MEETING DATE: June 12, 2017

AGENDA ITEM:	
PA16-036 Surface Water Comprehensive Plan Update	
PREPARED BY:	DIRECTOR APPROVAL:
Matthew Eyer, Surface Water Administrator	
DEPARTMENT:	
Public Works	
ATTACHMENTS:	
1. Memo to Council 2. Planning Commission Minutes from November 9, 2016 Workshop 3. Planning Commission Minutes from January 10, 2017 Public Hearing 4. Ordinance No. _____ 5. Completed 2015 Surface Water Comprehensive Plan Update	
BUDGET CODE:	AMOUNT:
NA	NA
SUMMARY:	

Gray & Osborne, Inc. was hired by the City to provide an update to the 2009 City of Marysville Surface Water Management Plan (Plan).

The updated Plan identifies surface water capital improvement projects utilizing existing surface water system maps, past studies, past reports, City work order records, staff interviews, models developed and other relevant information. A capital improvement program project implementation schedule has been created for the City through the year 2023.

The City's Planning Commission held a public workshop on November 9, 2016 and a public hearing on January 10, 2017 to accept public comments and review the Plan following public notice. As reflected in the minutes from the public hearing, dated January 10, 2017, the Planning Commission recommends Council adopt the Plan by ordinance. An ordinance has been prepared by city staff, has been reviewed by the City's Attorney and is attached.

RECOMMENDED ACTION: Affirm the Planning Commission's recommendation and adopt the Surface Water Comprehensive Plan Update by ordinance.



PUBLIC WORKS
Kevin Nielsen, *Director*

80 Columbia Avenue
Marysville, Washington 98270
Phone (360) 363-8100
Fax (360) 363-8284
marysvillewa.gov

MEMORANDUM

Date: May 10, 2017

To: City Council

From: Matthew Eyer, Surface Water Administrator

RE: Surface Water Comprehensive Plan Update

The City of Marysville Surface Water Comprehensive Plan (Plan) is a planning document that provides guidance to minimize adverse effects of stormwater runoff on ground and surface water in a manner that complies with federal, state, remove, and local surface water regulations. It identifies water quality and quantity problems associated with stormwater runoff that may affect the environment and community and provides recommendations for improvements and programs including a financial analysis and implementation schedule.

The Plan identifies specific structural and nonstructural solutions to quantity and water quality problems within the City. Structural solutions include construction of capital projects such as stormwater detention and treatment facilities, infiltration facilities, pipelines, and culverts. Nonstructural solutions include stormwater management facility inspection and maintenance, public education and outreach, water quality monitoring, implementation of best management practices (BMPs), and regulations encouraging vegetation preservation and low impact development.

Below are a few highlights of the 2016 Water System Plan:

- Final Plan obtained from Gray & Osborne on December 13, 2016
- Plan consists of:
 - Basic Planning Data (Topography, Drainage Basins, Soils, Wetlands)
 - Stormwater management system analysis
 - Existing system
 - Identified conveyance problems
 - Capital Improvement Plan
 - Simplified Financial Review
- Identified Conveyance Problems
 - Separated capital improvement projects by drainage basin
 - 25 capital improvement projects total
(as summarized below and as detailed in Table 4-1 of the Draft Plan)

Capital Improvement Projects by Basin						
Basin	Total No. of Projects	Pipe Replacement/ Installation	Bridge	Regional Detention/ Water Quality	Fish Screen	Creek Realignment
Quilceda Creek	18	7	3	4	1	3
Allen Creek	4	4				
Ebey Slough North	2			2		
Ebey Slough South	0					
Sunnyside Creek	1	1				
Total:	25	12	3	6	1	3

- **Capital Improvement Plan**

- Detailed cost estimates were developed for each project
- A summary of the costs per basin are shown below

Capital Improvement Project Costs		
Basin	Total No. of Projects	Project Costs
Quilceda Creek	18	\$55,939,000
Allen Creek	4	\$2,036,000
Ebey Slough North	2	\$8,358,000
Ebey Slough South	0	\$0
Sunnyside Creek	1	\$1,590,000
Total:	25	\$67,923,000

- **Financial Review**

- 6 Year CIP created (see table below)

6-Year CIP 2017-2023 ⁽¹⁾	
ES1: Historic Downtown Green Retrofit Study	2017 \$150,000
QC13: Culvert Removal and Bridge Installation along Quilceda Creek at State Avenue	2018 \$6,755,000
ES2: Water Quality Treatment Facility at Downtown Marina Outfall	2018 \$8,208,000
QC4B: Conveyance for Regional Pond 2	2019 \$4,901,000
QC5C: Edgecomb Creek Regional Detention Facility	2021 \$5,054,000
QC5B: Edgecomb Creek Conveyance	2022 \$8,517,000
QC5A: Edgecomb Creek Channel Realignment	2023 \$19,042,000

(1) Project costs reflect estimated Year 2016 costs. A cost escalation of approximately 3 percent should be used when budgeting for this project.

- Simplified financial analysis conducted (Table 5-4 in Draft Plan)
 - Results:
 - An annual increase of rates at 2% covers operating expenses.
 - An annual increase of rates at 2% (with no increase in connection fees) does not cover the anticipated capital improvement costs over the next 6 years.

PLANNING
COMMISSION



MINUTES

November 9, 2016

7:00 p.m.

City Hall

CALL TO ORDER

Chair Leifer called the November 9, 2016 meeting to order at 7:00 p.m. noting the absence of Kelly Richards.

Roll Call

Chairman: Steve Leifer

Commissioners: Roger Hoen, Kay Smith, Brandon Whitaker, Jerry Andes, Tom Thetford, Kelly Richards

Staff: Community Development Director Dave Koenig, Senior Planner Angela Gemmer, City Engineer Jeff Laycock, Project Engineer Ryan Morrison, Water Resources Manager Kari Chennault, Surface Water Specialist Matthew Eyer

Absent:

APPROVAL OF MINUTES

October 25, 2016

Chair Leifer requested that two corrections be made to the minutes to clarify the intent of the statements made.

Motion made by Commissioner Smith, seconded by Commissioner Richards, to approve the October 25 Meeting Minutes as corrected.

Commissioner Richards arrived at 7:05.

Motion passed unanimously (7-0), to approve the minutes as corrected.

AUDIENCE PARTICIPATION

None

PUBLIC HEARING

School District's 2016-2021 Capital Facilities Plan

Chair Leifer opened the hearing at 7:06 p.m. Ms. Gemmer explained what the requirements were for school impact fees to be collected by school districts. The districts had submitted CFP's that met all the required criteria. She then described the criteria that had to be met, and stated that all required elements for approval had been addressed. Lake Stevens School District was utilizing a local discount in their plan this year to determine fees due to a large increase in the school impact fee. The large increase is based on the need to construct new elementary school and new classrooms to the existing high school. In order to mitigate the impacts of a large increase in fees, a local discount was being proposed to balance the needs of the school district with the impacts to future residents and developers

Ms. Gemmer overviewed each of the districts' proposed impact fee changes. Staff is requesting Planning Commission make a recommendation to City Council to approve the plans as presented.

Chair Leifer stated that all of his curiosities had been satisfied at the previous meetings when each district presented their individual plans.

Commissioner Hoen questioned why Lake Stevens was in the Marysville Plan. Ms. Gemmer explained the reason for this; being the boundaries don't always neatly coincide with City limit boundaries. Director Koenig added that school district boundaries are separate from City boundaries, and that as the City has grown, it has grown into other school district boundaries.

Public Comment – None

Motion made by Commissioner Richards, seconded by Commissioner Smith, to forward this to the City Council with a recommendation for approval. **Motion** passed unanimously (7-0).

The public hearing was closed at 7:15 p.m.

NEW BUSINESS

Water Comprehensive Plan

Mr. Morrison began an explanation of the Comp Plan and described the update process for the plan. Mr. Morrison gave a presentation of the current water service provided by the City, including the current water service area and types of connections, as well as consumption history and demand and projected consumption for the future. He then

described the proposed improvements to the water system that would be required in the future and the costs associated with those improvements. Mr. Morrison explained that the plan focused on the use of City sources in order to limit the reliance on the Everett system, which comes at a much higher cost.

Chair Leifer questioned a recent Tribe funded water main and how the diversion to the Tribes would be reduced. Morrison and Laycock commented that once that line went active, it would likely reduce the City's contribution. Chair Leifer also asked if the water system contributed to the general fund or if rates were just enough to cover costs. Mr. Morrison and Laycock explained that the capital fees funded the infrastructure and that the rates covered the needs of the system.

Commissioner Richards questioned what the Arlington Christian School box on the map meant. Mr. Morrison explained that they receive water from Marysville. He also questioned whether fluoride in City water was necessary. Mr. Morrison commented that Marysville does not fluoridate its water, though the Everett water supply does. Ms. Chennault added that there is not a hard boundary between water systems, so it is difficult to tell the percentage of fluoride. Generally, the further north you are in the City, the less fluoride in the water.

Mr. Laycock discussed the work being done to ensure adequate supply and flow in the 83rd and 87th Ave. area to accommodate the expected development in that area. There was discussion about any plans to increase pressure north of 100th Street. Ms. Chennault noted that the plan had looked for any deficiencies throughout the City and that any areas with psi below 40 had been identified. The area Chair Leifer mentioned was approximately 55 psi, so was not identified as deficient in the plan.

It was noted that there was sufficient water for the anticipated population growth.

Stormwater Comprehensive Plan

Mr. Eyer described the current stormwater system. The system is regulated by DOE. He explained that we are in the middle of a permit cycle, so the planned goals are to look at any deficiencies in the system and how to correct them. The entire system underwent analysis and concerns were identified. He overviewed the results of the analysis, including a total of 25 projects identified. A six year plan was developed to address the 25 projects identified as well as the potential funding sources to address the issues identified. Mr. Eyer overviewed each of the projects. He explained the financial review included in the plan.

Commissioner Thetford questioned if the total for the water treatment facility project included the grant funds. Mr. Eyer replied that it did, and if the grant funding were not received, the project would not be feasible without a grant.

Commissioner Whitaker asked if the list of CIP projects submitted with the Municipal Permit annual reports to DOE were included in the Surface Water Plan update. Mr. Eyer responded that the stormwater comp plan was a bit unlike the water and sewer comp

plans in that there is not a RCW requirement or permit requirement to include that and that was why they tried to streamline it and not include anything that was not useful.

Chair Leifer questioned the remaining capacity in the stormwater ponds. Mr. Eyer replied that Pond 1 is at capacity, and Pond 2 had 147 acres of developable land capacity still available. There was discussion on whether pond 1 acreage that had been paid for but that was not currently being used. Ms. Chennault added that the ordinance required a building permit be obtained in order to buy into the pond and that many properties obtained a grading permit, but did not necessarily have civil plans or an actual planned project at this time. Low Impact Design methodologies were discussed including how the expected new requirements to utilize these methodologies would affect someone that had already bought into the pond. Ms. Chennault responded that the ponds themselves are a low impact development feature and that she was hopeful this fact could be utilized to meet some of the requirements.

Chair Leifer commended staff on the work and thoroughness of the presentations.

CITY COUNCIL AGENDA ITEMS AND MINUTES

ADJOURNMENT

Motion made by Commissioner Richards, seconded by Commissioner Thetford, to adjourn the meeting at 7:51 p.m. **Motion** passed unanimously.

NEXT MEETING – November 22



Amy Hess, Recording Secretary

PLANNING COMMISSION



MINUTES

January 10, 2017

7:00 p.m.

City Hall

CALL TO ORDER

Chair Leifer called the January 10, 2017 meeting to order at 7:00 p.m.

Marysville

Chairman: Steve Leifer

Commissioners: Roger Hoen, Jerry Andes, Kay Smith, Kelly Richards, Brandon Whitaker

Absent: Commissioner Tom Thetford (excused)

Staff: Community Development Director Dave Koenig, Senior Planner Angela Gemmer, Senior Planner Cheryl Dungan, Project Engineer Ryan Morrison, Surface Water Specialist Mathew Eyer

APPROVAL OF MINUTES

December 13, 2016

Commissioner Richards noted he would be abstaining from the vote as he was not present at the December 13 meeting.

Motion made by Commissioner Hoen, seconded by Commissioner Andes, to approve the December 13, 2016 Meeting Minutes. **Motion** passed (5-0) with Commissioner Richards abstaining.

AUDIENCE PARTICIPATION

Evan Kaiser, 2910 73rd Avenue NE, Marysville, WA, commented that when information is submitted to the Planning Commission all the pertinent documents should be submitted. He suggested that the Planning Commission conduct research on what other cities are doing when working on their codes. He asked if he could send emails to the

Planning Commission through Janis at the Planning Department and expect a reply in a reasonable time period. Chair Leifer replied that would be appropriate.

PUBLIC HEARING

A. City of Marysville – Water System Plan

Project Engineer Ryan Morrison made a PowerPoint presentation reviewing the Water System Plan Update.

Chair Leifer asked about adequate pressures for fire suppression equipment in the area north of 116th up to 152nd as referred to in his discussions with the fire marshal. His understanding is that there is still an issue with adequate pressure and fire flow. Project Engineer Morrison said he wasn't aware of any broad low pressure issues or fire flow issues in that area. Chair Leifer commented he heard there is a marginal amount of flow available. Project Engineer Morrison reviewed fire flow requirements and data and explained that the consultant highlighted deficiencies as part of the Water Plan but that area was not highlighted. Chair Leifer asked about the commercial industrial area. Project Engineer Morrison reviewed the commercial fire flow requirements. Chair Leifer summarized that the maximum they can get out of these is 2000 gpm, but the requirement is 2500 gpm. Project Engineer Morrison explained that that the maximum is calculated per port, but it is expected that there will be multiple hydrants which makes it workable.

Commissioner Hoen expressed concern about involvement of water drawing agencies in the water system plan update. Project Engineer Morrison replied that all the surrounding jurisdictions as well as the Department of Health have copies of this Plan and are invited to review and comment. This is the same for other jurisdictions. They are also in communication with the Fire Department about the fire flow.

Commissioner Hoen asked about the status of the water lines in the City. Project Engineer Morrison replied that most of the water main is ductile iron, but some of it is asbestos cement or cast iron. Asbestos cement is the oldest portion. This is on a schedule for maintenance as part of the renewals and replacement. They are replaced depending on prioritization and budgeting. Commissioner Hoen asked if available water for the system was predicted to be adequate through 2036. Project Engineer Morrison affirmed that it is.

Commissioner Richards asked if the Sunnyside Well will relieve the city of the need for Everett water. Project Engineer Morrison replied that it will not, and the City will want to keep that intertie in place. Commissioner Richards suggested talking to Everett about stopping adding fluoride to the water.

The public hearing was opened at 7:20 for public testimony. Hearing no comments, the hearing was closed at 7:20 p.m.

Commissioner Hoen noted that there are several areas that are expanding in Lakewood. He asked if staff believes there is adequate water planned to get water to the new facilities. Project Engineer Morrison affirmed that there is.

Motion made by Commissioner Richards, seconded by Commissioner Smith, to forward this item to Council with a recommendation for approval. **Motion** passed unanimously (6-0).

B. City of Marysville – Surface Water Comprehensive Plan

Surface Water Specialist Matthew Eyer made a presentation reviewing the Surface Water Comprehensive Plan Update. He explained that there are 25 projects identified as needed in the future. Five major projects have been identified for the next six years: Historic Downtown Green Retrofit Study, Culvert Removal and Bridge Installation along Quilceda Creek at State Avenue, Water Quality Treatment Facility at Downtown Marina Outfall, Conveyance for Regional Pond 2, and Edgecomb Creek Regional Detention Facility. The simplified financial review showed that the 2% annual rate increase will cover the operating increase, but not the capital projects.

Commissioner Hoen asked if the impact fees are adequate. Senior Planner Gemmer stated that impact fees are not expected to cover all expenses. Other funding mechanisms help finance projects.

Chair Leifer asked about the area near 152nd near the Edgecomb detention pond. He asked if the total anticipated volume has taken into account the requirements for Low Impact Development and that a portion of the water will be going into the ground. Surface Water Specialist Matthew Eyer stated that would be taken into consideration going forward with any new pond. Staff hasn't looked into how a new pond would look under the new manual. As it currently stands, the pond is designed to take all the water from all the sites.

Chair Leifer asked about money for realignment of Edgecomb Creek. He asked if a route has been established. Surface Water Specialist Matthew Eyer clarified it was Hayho Creek which is the barrier, not Edgecomb. Edgecomb Creek has some theoretical language in the Comprehensive Plan about the potential realignment. Senior Planner Dungan explained that Otak developed a plan on possibilities for that. She explained that during the recession a lot of the properties went back to the banks. The City backed away from this due to lack of interest from the property owners and is no longer pursuing it at this time.

The public hearing was opened at 7:41 for public testimony. Hearing no comments, the hearing was closed at 7:41 p.m.

Motion made by Commissioner Andes, seconded by Commissioner Richards, to forward this item to Council with a recommendation for approval. **Motion** passed unanimously (6-0).

NEW BUSINESS

A. Code Amendment – Flagpoles

Senior Planner Gemmer reviewed the proposed amendments to how the City deals with flags and flagpoles. She reviewed background on this item and explained that the majority of Washington jurisdictions researched are silent on flagpole regulations with the exception of Spokane. Staff is proposing regulations adapted from Spokane's. She reviewed three different options for flagpole definitions. She also reviewed other proposed changes.

There were clarification questions regarding the language under 22C.010.220 Height-Exceptions to limits (3). Staff noted they would review the language for clarifications.

Commissioner Richards asked how tall a flagpole could be on top of his house. Director Koenig replied they would look into that, but currently it would be as high as the zone allows.

Commissioner Andes referred to the proposed language for setbacks and suggested they just keep it the same as the property setbacks. Senior Planner Gemmer indicated they could, but noted that some setbacks are much bigger, up to 20 feet. Commissioner Andes recommended keeping it the same as building setbacks to keep it simple.

Commissioner Hoen asked about vertical sail-type flags that he has seen around which are used for advertising. Senior Planner Gemmer replied that those are generally prohibited in the code and present an ongoing code enforcement issue. They are considered signs, not flags.

Chair Leifer referred to item 11 under 22C.160.180 Exemptions in the Sign Code and stated he would like to see preference given to the United States flag by giving it an additional height allowance above and beyond all others. Director Koenig commented that the intent is not to get into regulating college flags, 12th man flags, etc. The etiquette of flags requires that the US flag is to be flown on top above all others. Language relating to this can be added.

Commissioner Richards agreed with the standard regarding the US flag, but noted that people will use this as a statement. Senior Planner Gemmer suggested getting legal guidance on whether or not this is something that can be regulated.

B. 2017-2022 - - Draft Capital Facilities Plan

Senior Planner Dungan introduced the Capital Facilities Plan for 2017-2022 as contained in the Planning Commission packet.

Commissioner Whitaker asked how the projects are prioritized. Senior Planner Dungan stated that there is a rating system within the City's database to help determine this. The plan is changed every two years in response to changes in these priorities.

Commissioner Whitaker asked what is behind the justification for moving forward with the project. Senior Planner Dungan replied that they are policies and goals that are outlined in the Comprehensive Plan and through the Growth Management Act. Commissioner Whitaker asked how estimates are made for construction of projects that are out in the future. Senior Planner Dungan replied that they are based on best case estimates.

Commissioner Richards noted that some of these are budgeted for, but some are not. Senior Planner Dungan explained that they will be depending on grant funding for a lot of things.

Commissioner Hoen noted that sidewalks continue to be discussed as something that is lacking in the City. He asked if there is part of a plan that says we are going to do a certain amount of sidewalks. Senior Planner Dungan replied that there is an allowance for sidewalks in the maintenance code. In the zoning code under residential density incentives there are additional bonus credits given to developers if they do off-site sidewalk improvements. Senior Planner Gemmer commented that with any new projects there is an expectation that frontage improvements will be done. Moving forward the situation should be improving. Also, in the existing Transportation Plan which was adopted in 2015 there is prioritization of where the City wants sidewalks constructed.

Chair Leifer referred to the potential options for improvements around Geddes Marina and asked if the third one assumes that the previous ones were completed. Senior Planner Dungan explained that there are steps that need to be completed. Cleanup of the site is the first step. The park will likely be constructed in phases as funding allows. Director Koenig explained that this reflects the Council's direction relating to the budget. Senior Planner Dungan commented that the Capital Facilities Plan as presented was adjusted to address Council's wishes related to budget discussions.

Chair Leifer commented that it appears that the improvements to Public Works would allow the existing building to be utilized by other uses, and a new facility for Public Works would be constructed. Director Koenig didn't think there was a new facility or expansion planned for Public Works. Senior Planner Dungan commented that Sanitation is relocating some of their trucks onto the old mill site that is adjacent.

Chair Leifer asked if Public Safety is the planned site for the new facility. Director Koenig commented that they don't have a site yet for the new facility, but there are also some fire uses there. He noted that this project is complicated by the Regional Fire Authority issue right now.

Commissioner Andes asked if water and road improvements would be done at the same. Senior Planner Dungan replied that typically they would be, but noted that someone from Public Works will be present at the hearing to answer questions.

Motion made by Commissioner Richards, seconded by Commissioner Andes, to schedule this for a public hearing. **Motion** passed unanimously (6-0).

CITY COUNCIL AGENDA ITEMS AND MINUTES

ADJOURNMENT

Motion made by Commissioner Smith, seconded by Commissioner Richards, to adjourn the meeting at 8:28 p.m. **Motion** passed unanimously (8-0).

NEXT MEETING:

January 24, 2017



Angela Gemmer, Senior Planner, for
Laurie Hugdahl, Recording Secretary

**CITY OF MARYSVILLE
Marysville, Washington**

ORDINANCE _____

**AN ORDINANCE OF THE CITY OF MARYSVILLE, WASHINGTON,
ADOPTING AN UPDATE TO THE CITY'S SURFACE WATER
COMPREHENSIVE PLAN.**

WHEREAS, the Marysville City Council finds that it is necessary, appropriate, and in the public interest and welfare to promote and provide needed public storm and surface water facilities, as well as other stormwater related programmatic services and capabilities, to address existing drainage problems, and to allow continued future development throughout the City; and

WHEREAS, the City of Marysville's existing Surface Water Management Plan was approved by Ordinance No. 2808 on December 14, 2009; and

WHEREAS, the City of Marysville commissioned a qualified consultant (Gray and Osborne, Inc.) to prepare an update to the Surface Water Management Plan, which Plan is now being referred to as the Surface Water Comprehensive Plan Update; and

WHEREAS, following public notice, on December 7, 2016, the City issued Addendum No. 27 to the Final Environmental Impact Statement for the City of Marysville Comprehensive Plan, addressing the environmental impacts of the Surface Water Comprehensive Plan Update;

NOW THEREFORE, the City Council of the City of Marysville, Washington, do ordain as follows:

Section 1. The City of Marysville Surface Water Comprehensive Plan Update, prepared by Gray & Osborne, Inc. and dated December 2016, is hereby adopted as set forth in the attached Exhibit A. A copy of the Surface Water Comprehensive Plan Update shall be made available for inspection and review at the office of the City Clerk and the office of Community Development.

Section 2. **Severability.** If any section, subsection, sentence, clause, phrase, or word of this ordinance is held to be invalid or unconstitutional by a court of competent jurisdiction, such invalidity or unconstitutionality thereof shall not affect the validity or constitutionality of any other section, subsection, sentence, clause, phrase, or word of this ordinance.

Section 3. **Effective Date.** This ordinance shall become effective five days after the date of its publication by summary.

PASSED by the City Council and APPROVED by the Mayor this ____ day of _____, 2017.

CITY OF MARYSVILLE

By _____
MAYOR

ATTEST:

By _____
DEPUTY CITY CLERK

APPROVED AS TO FORM:

By _____
CITY ATTORNY

Date of Publication:

Effective Date:

CITY OF MARYSVILLE

SNOHOMISH COUNTY

WASHINGTON



SURFACE WATER COMPREHENSIVE PLAN UPDATE

G&O #15550
DECEMBER 2016



Gray & Osborne, Inc.
CONSULTING ENGINEERS

CITY OF MARYSVILLE

SNOHOMISH COUNTY

WASHINGTON



SURFACE WATER COMPREHENSIVE PLAN UPDATE



G&O #15550
DECEMBER 2016



Gray & Osborne, Inc.
CONSULTING ENGINEERS

TABLE OF CONTENTS

CHAPTER 1 - INTRODUCTION	1
PURPOSE.....	1
GOALS	2
CHAPTER 2 - SERVICE AREA CHARACTERISTICS	3
LOCATION.....	3
TOPOGRAPHY.....	3
DRAINAGE BASINS.....	3
Waterways and Water Bodies	4
SOILS.....	4
POPULATION TRENDS.....	6
ZONING AND LAND USE	6
CLIMATE.....	8
CRITICAL AREAS.....	8
Wetlands.....	8
Aquifer recharge areas	10
Fish and wildlife Habitat areas	10
Geologically hazardous areas.....	12
STORMWATER UTILITY SERVICES	12
CHAPTER 3 - STORMWATER MANAGEMENT SYSTEM	
ANALYSIS.....	13
INTRODUCTION	13
EXISTING STORMWATER MANAGEMENT SYSTEM.....	13
REFERENCED REPORTS	13
WATER QUALITY.....	13
CITY IDENTIFIED STORMWATER CONVEYANCE PROBLEMS	14
Hydrologic Model.....	14
Hydraulic Model.....	14
DRAINAGE BASINS	15
IDENTIFIED DEFICIENCIES.....	15
Quilceda Creek Basin	16
QC1 Stormwater Pipe Damage at Edward Springs Reservoir.....	16
QC2 (Formerly MQ-HH-19) Irrigation Ditch Accessible to Fish	
Upstream of 160 th Street NE.....	16
QC3 (Formerly MQ-EC-03, MQ-EC-05) Undersized Field Access	
Culvert along Edgecomb Creek	16
QC4A (Formerly MQ-HH-16) Hayho Creek Channel Mitigation (North	
Marysville Master Drainage Plan)	16
QC4B (Formerly MQ-HH-32) Conveyance for Regional Detention	
Pond 2	17

QC4C (Formerly MQ-HH-32) Hayho Creek Regional Detention Pond 3	17
QC5A (Formerly MQ-EC-13) Edgecomb Creek Channel Mitigation (North Marysville Master Drainage Plan)	17
QC5B (Formerly MQ-EC-13) Edgecomb Creek Conveyance (North Marysville Master Drainage Plan)	18
QC5C (Formerly MQ-EC-13) Edgecomb Creek Channel Mitigation (North Marysville Master Drainage Plan)	18
QC6 (Formerly MQ-EC-01) Undersized Culvert along Edgecomb Creek at 152 nd Street NE.....	18
QC7 (Formerly MQ-MQ-07) Undersized Culvert along Olaf Strad Creek at 152 nd Street NE.....	18
QC8 (Formerly MQ-MQ-04) Undersized Culvert and Diminished Habitat along Quilceda Creek at Strawberry Fields Trail	19
QC9 (Formerly MQ-HH-09) Flooding of 43 rd Avenue and Emerald Hills Estates.....	19
QC10 (Formerly MQ-HH-38) Channel Erosion on Hayho Creek between the Burlington Northern Santa Fe Railroad and 47 th Drive NE.....	19
QC10A Flooding of 136 th Street NE at 45 th Avenue NE	19
QC11 (Formerly WQ-WQ-08) Undersized Culvert along a Tributary to West Fork Quilceda Creek at 104 th Street NE	20
QC12 (Formerly WQ-WQ-09) Undersized Culvert along a Tributary to West Fork Quilceda Creek at 103 rd Street NE	20
QC13 (Formerly MQ-QC-09) Undersized Culvert along Quilceda Creek at State Avenue	21
QC14 (Formerly MQ-QC-12) Undersized Culvert along Quileeda Creek at BNSF Railroad	21
Allen Creek Basin.....	23
AC1 (Formerly AC-AC-10) Undersized Stormwater Pipes at 95 th Street NE and 67 th Avenue NE.....	23
AC2 (Formerly AC-AC-03) Undersized Culvert and Erosion of the Stream Bank Along Allen Creek at 88 th Street NE	23
AC3 (Formerly AC-JC-12) Undersized Stormwater Pipes at 61 st Street NE Cul-de-Sac	23
AC4 (Formerly AC-JC-11) Undersized Stornwater Pipes at 60 th Place NE and the Surrounding Area	24
Ebey Slough North Basin.....	25
ES1 Historic Downtown Green Retrofit Study.....	25
ES2 (Formerly ES-DT-03) Water Quality at Downtown Marina Outfall Study	25
King Creek Basin.....	27
KC1 Undersized Culvert Along King Creek at Soper Hill Road	27

CHAPTER 4 - CAPITAL IMPROVEMENT PLAN.....	29
INTRODUCTION	29
CAPITAL IMPROVEMENT PROJECTS	29
Quilceda Creek Basin Projects	31
QC1: Stormwater Pipe Replacement at Edward Springs Reservoir	31
QC2: Fish Screen Installation Along Hayho Creek at 160 th Street NE....	31
QC3: Field Access Culvert Replacement along Edgecomb Creek	31
QC4A: Hayho Creek Channel Realignment (North Marysville Master Drainage Plan)	31
QC4B: Conveyance for Regional Detention Pond 2 (North Marysville Master Drainage Plan)	32
QC4C: Hayho Creek Regional Detention Pond 3	32
QC5A: Edgecomb Creek Channel Realignment (North Marysville Master Drainage Plan)	32
QC5B: Edgecomb Creek Conveyance (North Marysville Master Drainage Plan).....	32
QC5C: Edgecomb Creek Regional Detention Facility (North Marysville Master Drainage Plan)	33
QC6: Culvert Replacement along Edgecomb Creek at 152 nd Street NE... 33	
QC7: Culvert Replacement along Olaf Strad Creek at 152 nd Street NE ... 33	
QC8: Culvert Replacement and Channel Restoration along Middle Fork Quilceda Creek at Strawberry Fields Trail	33
QC9: Berm Installation at 43 rd Avenue and Emerald Hills Estates	34
QC10: Stabilization of Hayho Creek between the BNSF Railroad and 47 th Drive NE	34
QC10A: Runoff Storage Along 136 th Street NE at 45 th Avenue	34
QC11: Culvert Removal and Bridge Installation at 104 th Street NE	34
QC12: Culvert Removal and Bridge Installation at 103 rd Street NE	34
QC13: Culvert Removal and Bridge Installation Along Quilceda Creek at State Avenue	35
Allen Creek Basin	37
AC1: Storm Pipe Replacement at 95 th Street NE and 67 th Avenue NE ... 37	
AC2: Culvert Replacement and Erosion Control Measures at 88 th Street NE	37
AC3: Storm Pipe Replacement at 61 st Street NE Cul-de-Sac.....	37
AC4: Storm Pipe Replacement at 60 th Place NE and Surrounding Area ... 37	
Ebey Slough North Basin	39
ES1: Historic Downtown Green Retrofit Study.....	39
ES2: Water Quality Treatment Facility at Downtown Marina Outfall 39	
King Creek Basin.....	41
KC1: Culvert Replacement along King Creek at Soper Hill Road.....	41

CHAPTER 5 - FINANCIAL REVIEW	47
Stormwater Utility	47
Capital Improvement Plan.....	48
Operations and maintenance and Equipment Purchase	50
Service Charge Determination	51
Preliminary Rate Analysis.....	51
Grant and Loan Programs	54
Public Works Trust Fund.....	54
Department of Ecology Integrated Funding Program	54
Debt Financing	54
Future Capital Improvement Plan.....	55
Appendix A - Stormwater Base Map.....	57
Appendix B - Cost Estimates	59

LIST OF TABLES

<u>No.</u>	<u>Table</u>	<u>Page</u>
2-1	Soil Characteristics	5
2-2	Population	6
2-3	Land Use	7
2-4	Average Monthly Climate Data.....	8
2-5	Wetland Buffer Widths	10
2-6	Stream Classifications and Buffer Width.....	11
3-1	Drainage Basin Summary	15
4-1	Capital Improvement Projects	43
4-2	Capital Improvement Plan (2017 to 2022).....	46
5-1	Planned Capital Improvements 2017-2023	49
5-2	2015 Operating and Maintenance Expenses	50
5-3	Budget Forecast Assumptions and Baseline Operating Costs	51
5-4	Financial Analysis	53

LIST OF FIGURES

<u>No.</u>	<u>Figure</u>	<u>Follows Page</u>
2-1	Vicinity Map.....	4
2-2	Topography Map	4
2-3	Drainage Basins Map	4
2-4	NRCS Soil Survey Map	4
2-5	Future Land Use Map	6
2-6	Wetlands Map.....	10
2-7	Stream Classes Map.....	12
2-8	Geologic Hazard Areas	12
3-1	Existing Stormwater Facilities	14
3-2	Identified Deficiencies Quilceda Creek Basin North	22
3-3	Identified Deficiencies Quilceda Creek Basin South	22
3-4	Identified Deficiencies Allen Creek Basin.....	24
3-5	Identified Deficiencies Ebey Slough Basin North.....	26
3-6	Identified Deficiencies King Creek Basin.....	28
4-1	CIP Projects.....	30
4-2	CIP Projects (QC1).....	36
4-3	CIP Projects (QC2).....	36
4-4	CIP Projects (QC3).....	36
4-5	CIP Projects (QC4).....	36
4-6	CIP Projects (QC5).....	36
4-7	CIP Projects (QC6).....	36
4-8	CIP Projects (QC7).....	36

<u>No.</u>	<u>Figure</u>	<u>Page</u>
4-9	CIP Projects (QC8).....	36
4-10	CIP Projects (QC9).....	36
4-11	CIP Projects (QC10, QC10A).....	36
4-12	CIP Projects (QC11).....	36
4-13	CIP Projects (QC12).....	36
4-14	CIP Projects (QC13).....	36
4-15	CIP Projects (AC1).....	38
4-16	CIP Projects (AC2).....	38
4-17	CIP Projects (AC3).....	38
4-18	CIP Projects (AC4).....	38
4-19	CIP Projects (ES1).....	40
4-20	CIP Projects (ES2).....	40
4-21	CIP Projects (KC1).....	42

CHAPTER 1

INTRODUCTION

Prior to the late 1970s, stormwater management in the U.S. and specifically the Puget Sound region consisted primarily of conveying runoff away from developed areas in order to preserve the health and safety of citizens and protect property, both public and private. Drainage improvement projects addressed large storm events and local flooding with little thought for upstream, downstream, or environmental impacts. With the passage of the Clean Water Act in 1972, completion of the Nationwide Urban Runoff Program in 1983, and subsequently other federal and state laws, the cumulative effects of smaller storms in developed/urbanized areas were formally recognized as a major contributor to water quality and habitat degradation.

Stormwater runoff picks up and carries sediment and pollutants from exposed construction sites and agricultural areas and pollutants from residential, commercial, and industrial developments. Pollutants in stormwater runoff include metals such as lead, cadmium, and copper; oil and grease; pesticides and fertilizers; nutrients; suspended solids; and harmful bacteria. In addition, urbanization increases the amount of impervious surfaces such as rooftops, streets, and parking areas. Impervious surfaces directly relate to an increase in runoff volumes and peak flow rates. The pollutant loads and increased volumes of stormwater runoff result in negative impacts to downstream properties and surface water bodies such as lakes, streams, and wetlands and reduced infiltration to groundwater. Due to regulations required under the Clean Water Act and the listing of anadromous (salmon, trout, char) species under the Endangered Species Act, it has become increasingly important for municipalities to implement stormwater quality and quantity (flow) control measures.

The City of Marysville last adopted its Surface Water Comprehensive Plan in 2009. The City population has grown from approximately 25,000 in 2002 to approximately 63,000 today, primarily through annexation. A significant portion of this growth has occurred since the completion of the 2009 Surface Water Comprehensive Plan when the City annexed the majority of its Urban Growth Area (UGA) in December of 2009.

PURPOSE

The City of Marysville Surface Water Comprehensive Plan (Plan) is a planning document that provides guidance to minimize adverse effects of stormwater runoff on ground and surface water in a manner that complies with federal, state, and local surface water regulations. It identifies water quality and quantity problems associated with stormwater runoff that may affect the environment and community, and provides recommendations for improvements and programs including a financial analysis and implementation schedule.

The Plan identifies specific structural and nonstructural solutions to quantity and water quality problems within the City. Structural solutions include construction of capital projects such as stormwater detention and treatment facilities, infiltration facilities, pipelines, and culverts. Nonstructural solutions include stormwater management facility inspection and maintenance, public education and outreach, water quality monitoring, implementation of best management practices (BMPs), and regulations encouraging vegetation preservation and low impact development.

GOALS

As additional development and redevelopment occur within the City, the amount of naturally vegetated areas will decrease while the amount of impervious surfaces will increase, leading ultimately to increased peak runoff rates and transport of more pollutants to the City's streams, wetlands, and rivers.

The primary goal of the Marysville Stormwater Comprehensive Plan is to provide guidance to the City Council, staff, and citizens to preserve and protect the water quality and hydrologic regime within the City's natural and manmade surface and stormwater drainage system, and the major receiving waters, Ebey Slough and the Snohomish River.

To this end, the City intends to manage land development and stormwater programs to preserve natural areas, minimize contact with contaminants, mitigate the impacts of increased runoff, enforce the City's National Pollutant Discharge Elimination System (NPDES) permit conditions and erosion control BMPs on construction sites, and to preserve fish and wildlife habitat. The City's implementation of the Plan will meet the goals to protect the health, safety, and welfare of the local citizenry and to preserve surface water resources within the City.

CHAPTER 2

SERVICE AREA CHARACTERISTICS

LOCATION

The City of Marysville (City) was officially incorporated in Washington State in 1891 with a population of 350. It is located in Snohomish County, approximately 5 miles north of Everett and directly borders the City of Arlington to the north. The City's current boundary and Urban Growth Area (UGA) encompass approximately 21 square miles of land. Interstate 5 and State Routes 531, 528, and 539 pass through the City, while State Route 9 provides the border to the east. The Burlington Northern Santa Fe Railroad also runs north/south through the City. Figure 2-1 provides a vicinity map of the area.

Marysville is the second largest city in Snohomish County. Per the census conducted in 2010, the population was approximately 60,000, representing 8.4 percent of the total population of Snohomish County. In 2015, the population was estimated to be 65,000.

TOPOGRAPHY

Marysville lies between the Puget Sound and the Central Cascade Mountains, with Mount Pilchuck being a prominent fixture on the horizon. The south end of the City sits along Ebey Slough just before it discharges into Possession Sound along with Steamboat Slough and the Snohomish River (see Figure 2-2). The elevation within the City gradually slopes north to south along the I-5 corridor from 160 feet in the north end of the City to 5 feet at Ebey slough in the south end. This area is known as the Marysville Trough, which is an alluvial plain that runs through much of the City. The Tulalip Plateau borders the Marysville Trough to the west, and to the east is the Getchell Hill Plateau, reaching a maximum elevation of 465 feet on the eastern border of the Marysville city limits. In the Smokey Point neighborhood, on the north end of the city, the trough continues well beyond the City limits, maintaining fairly flat terrain throughout.

DRAINAGE BASINS

The City of Marysville is located within the Snohomish River Drainage Basin within Water Resource Inventory Area 7 (WRIA 7), the second largest watershed in the state. The basin encompasses 1,978 square miles west of the Cascade crest. As shown in Figure 2-3, four smaller drainage basins have been delineated around the City's drainage infrastructure: Quilceda Creek, Allen Creek, King Creek, and Ebey Slough. All four of these basins empty into Ebey Slough, which then joins with the Snohomish River near its drainage point into Possession Sound.

Quilceda Creek Basin encompasses 36.6 square miles, 9.3 square miles of which are located in the City and is the largest basin within the City. It runs north-south on the east side of the City and is predominately located within the Marysville Trough. It generally consists of till and outwash soils. Although outwash soils usually drain well, high groundwater in the winter months creates saturated soil conditions that impedes infiltration, and commonly results in a high rate of surface water runoff.

The second largest basin that lies within the Marysville UGA is the Allen Creek Basin. It has an overall area of 10.4 square miles, 7.7 of which are within the UGA boundary. The Allen Creek Basin makes up a large portion of the southeastern part of the City, having most of its area on the Getchell Plateau. The soils in the Allen Basin are very similar to that of the Quilceda Basin and have similar surface water runoff issues caused by high groundwater.

The other two basins, Ebey Slough Basin and King Creek Basin, are significantly smaller than the Quilceda and Allen Creek Basins, only making up 1.9 and 2.9 square miles respectively. The Ebey Slough Basin is contained entirely within the Marysville city limits on the south end and sits mostly within the Marysville Trough. The Sunnyside Basin sits atop the Getchell Plateau and extends south from the edge of the Marysville City limits with approximately half the basin contained within the city limits.


WATERWAYS AND WATER BODIES

The City of Marysville contains many waterways, most of which are within the Quilceda Creek and Allen Creek Basins. These waterways have been manipulated and channelized over the years and are highly susceptible to environmental problems such as pollution, erosion, and flooding. Non-point source pollution from agriculture and urban development have increased the presence of pesticides, animal waste, chemical fertilizers, sediments, heavy metals, detergents, and petroleum. Allen Creek and Quilceda Creek have been placed on Washington State's 303(d) list for fecal coliform, which requires them to have Total Maximum Daily Load (TMDL) cleanup plans. Low dissolved oxygen levels are also a concern in the summer months and can compromise crucial fish and wildlife habitat.

The Quilceda and Allen Creek systems are within the Tulalip Tribes' usual and accustomed fishing areas. Land use within these systems is therefore governed by a variety of tribal, state, county, and city governments.

SOILS


The soils of Snohomish County were surveyed by the United States Department of Agriculture (USDA) Natural Resources Conservation Service (NRCS). The NRCS website indicates 22 soil types within the UGA of Marysville, as shown in Figure 2-4 and Table 2-1.



Cities	Marysville City Limits	Streams
Arlington	Urban Growth Boundary	Water Bodies
Everett		
Lake Stevens		
Marysville		

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

VICINITY MAP
FIGURE 2-1




- Marysville City Limits
- Urban Growth Boundary
- 20 ft. contours
- Streams
- Water Bodies



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

TOPOGRAPHY MAP
FIGURE 2-2

CITY OF
Marysville
WASHINGTON



- | | |
|-------------------------|--------------------------|
| Basin Name | — Marysville City Limits |
| Allen Creek Basin | Urban Growth Boundary |
| Ebey Slough Basin North | Water Bodies |
| Ebey Slough Basin South | Streams |
| King Creek Basin | |
| Quilceda Creek Basin | |

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

DRAINAGE BASINS MAPS
FIGURE 2-3






TABLE 2-1

Soil Characteristics

Soil	Hydrologic Soil Group	Drainage Class Rating
Alderwood gravelly sandy loam	B	Moderately well drained
Alderwood-Everett gravelly sandy loams	B	Moderately well drained
Bellingham silty clay loam	C/D	Poorly drained
Custer fine sandy loam	C/D	Poorly drained
Everett very gravelly sandy loam	A	Somewhat excessively drained
Indianola loamy sand	A	Somewhat excessively drained
Kitsap silt loam	C	Moderately well drained
Lynnwood loamy sand	A	Somewhat excessively drained
McKenna gravelly silt loam	D	Poorly drained
Mukilteo muck	B/D	Very poorly drained
Norma loam	B/D	Poorly drained
Norma variant loam	C/D	Poorly drained
Pastik silt loam	C	Moderately well drained
Puget silty clay loam	C	Poorly drained
Ragnar fine sandy loam	A	Well drained
Snohomish silt loam	D	Poorly drained
Sumas silt loam	C	Poorly drained
Terric Medisaprists	C	Very poorly drained
Tokul silt loam	C	Moderately well drained
Tokul gravelly medial loam	B	Moderately well drained
Tokul-Winston gravelly loams	C	Moderately well drained
Xerorthents	B	Well drained

The Soil Classification System (SCS) classifies soils, from A to D, according to runoff potential. Type A has low runoff potential and high infiltration rates even when thoroughly wetted, and mostly consists of well to excessively drained sands or gravels. Type B consists of moderately well to well drained soils with moderately fine to moderately coarse texture and moderate infiltration rates when thoroughly wetted. Type C has low infiltration rates when thoroughly wetted with moderately fine to fine textured soils, and often have a layer that impedes downward movement of water. Type D has the highest runoff potential and very low infiltration rates when thoroughly wetted. It consists of clay soils with high swelling potential, soils with a permanent high water table, soils with a claypan or clay layer at or near the surface, and shallow soils over nearly impervious material. The SCS also provides information pertaining to the physical and chemical properties of the soils, including drainage class, which refers to the frequency and duration of wet periods under conditions similar to those under which the soil formed.

The northern region of the city predominantly contains low infiltration Type C and D soils.

The central area consists mostly of type A soils and the southeastern area consists mostly of type B soils, both having high to moderate infiltration and lower potential for runoff.

POPULATION TRENDS

Residential population for the City was estimated by the United States Census to be 60,202 in 2010. Per the City's 2015 Comprehensive Plan, it is estimated that approximately 65,000 people live within the City. The City Plan also creates a 20-year population growth target which estimates approximately 87,000 people in 2035. This estimate is based upon available land areas and existing zoning classifications within the City and UGA. Census data, proposed new residential units and sensitive areas were factored into the development of the growth rate.

Table 2-2 summarizes the historic population estimates based on the U.S. Census as well as the forecasted population estimates from the City's current Comprehensive Plan.

TABLE 2-2
Population


Year	Population
1980	5,080
1990	10,328
2000	25,315
2010	60,202 ⁽¹⁾
2015	65,087 ⁽¹⁾
2035	87,800 ⁽¹⁾

(1) Estimated.

ZONING AND LAND USE

The population in Marysville grew by approximately 137 percent between the year 2000 and 2010. Land use and zoning play an important role in determining growth patterns and, therefore, in the potential locations of future storm water facilities. Future land use and changing population densities, as directed by applicable zoning ordinances, can significantly impact a system's ability to provide adequate services to specific areas.

Marysville has a combination of residential, commercial, industrial and open space land uses as shown in Figure 2-5. This figure provides a map of future land use for the City as shown in the City's 2015 Comprehensive Plan. Residential zones make up two thirds of the Marysville UGA, and are positioned in the central and southeastern regions, with a small region in the Lakewood area as well. The open space areas are spread throughout the City, with the largest located in the south end of the City where Jones Creek and Allen Creek discharge into Ebey Slough.



The vast majority of the commercial and industrial property is on the west side of the City along I-5. New commercial and industrial development is occurring in the Lakewood and Smokey Point neighborhoods in the north, and in the Downtown area, located in the south end of the City. The development in the Smokey Point region has potential to have significant stormwater implications, as much of that land is currently being used for agriculture, but is zoned light industrial and could soon experience a significant increase in impervious surface. This change in impervious surface will require extensive storm water management to mitigate flooding and pollution of surface waters in the upper reaches of the Quilceda Creek Basin.

The land use classifications within the City are shown in Table 2-3.

TABLE 2-3

Land Use

Land Use Category	Acreage
R12 Multi-Family Low	362
R18 Multi-Family Medium	478
R28 Multi-Family High	71
R6-18 Multi-Family Low	156
R4.5 Single-Family Medium	3,948
R6.5 Single-Family High	3,441
R4-8 Single-Family High	142
R8 Single-Family High Small Lot	209
Business Park	92
Community Business	435
Downtown Commercial	162
General Commercial	650
General Industrial	324
Light Industrial	1,369
Neighborhood Business	15
Mixed Use	456
Public-Institutional	77
Recreation	340
Open	526

Overall, the city is 66.5 percent residential, 26.4 percent commercial and industrial, and 7.1 percent public land, recreation, and open space.

CLIMATE

Marysville receives an average of 37.5 inches of rain per year, two thirds of which falls in October through March. Table 2-4 provides historical monthly averages for temperature and precipitation as reported by NOAA from the Arlington Municipal Airport Weather Station.

TABLE 2-4

Average Monthly Climate Data

Month	High Temp.	Low Temp.	Precipitation (in.)
Jan	46°F	34°F	4.37
Feb	49°F	35°F	3.41
Mar	53°F	37°F	3.86
Apr	58°F	41°F	2.96
May	64°F	46°F	2.57
Jun	68°F	51°F	2.26
Jul	73°F	54°F	1.32
Aug	74°F	54°F	1.35
Sep	69°F	49°F	2.09
Oct	60°F	42°F	3.25
Nov	51°F	37°F	5.11
Dec	45°F	34°F	4.99
Total			37.54

CRITICAL AREAS

The City of Marysville Municipal Code (MMC 22E.010), identifies three categories of critical areas within its UGA: Wetlands, Fish and Wildlife Habitat areas, and Geologic Hazard Areas. These areas require special considerations and protections in order to preserve the functions that benefit the City and its residents, and to protect public health and safety from potential hazards. The aquifers that lie within the boundaries of the Marysville UGA do not fit the criteria of a critical area as defined by the Growth Management Act (RCW 36.70A.060) due to the fact that they are not used for potable water; however, they are discussed below because they play a significant role in stormwater drainage issues and are important in maintaining stream base flow, which impacts fish and wildlife habitat.

WETLANDS

As defined by MMC 22A.020.240 wetlands are areas that are inundated or saturated by surface water or ground water at a frequency and duration sufficient to support, and that

under normal circumstances do support, a prevalence of vegetation typically adapted for life in saturated soil conditions. This includes swamps, marshes, bogs, and similar areas, but excludes artificial wetland sites such as irrigation and drainage ditches, grass-lined swales, canals, detention facilities, farm ponds, landscape amenities, or any wetland unintentionally created by road construction after July 1, 1990. Artificial wetlands created intentionally for mitigation purposes are included in this definition and are protected under the critical areas ordinance.

Wetlands perform valuable functions within the ecosystem. Clearing of vegetation, grading, filling, draining, and other activities associated with land development may decrease the ability of the riparian zone to provide drainage, stabilize stream banks, provide wildlife habitat, and filter pollutants from runoff. Wetlands receiving surface water from surrounding areas can filter entering pollutants by a combination of physical, chemical, and biological processes.

Wetlands also play a major role in flood control. During flooding, rivers and streams overflow their banks and spread out across the flood plain. Wetlands attenuate the peak flows from storm events by storing water during wet periods and discharging this stored water later during drier periods. Wetlands also provide habitat and a source of food for fish and wildlife. Seventy-five percent of Western Washington's wildlife species use wetlands or riparian zones during some portion of their life cycle, and many species solely inhabit wetland areas.

Washington State Department of Ecology (Ecology) rates wetlands into four different categories (Categories I, II, III, and IV). These categories are based on the wetland's sensitivity to disturbance, rarity, functions they provide, and whether or not they are replaceable; Category I being the most crucial to protect. Within the UGA, Marysville has a total of 434 acres of known wetland area; 142 acres of Category I, 134 acres of Category II, 141 acres of Category III, and 18 acres of Category IV. Figure 2-6 depicts the delineation of all four wetland categories as provided by the City's GIS data, as reported from limited scope studies and from development. MMC 22E.010.100 establishes minimum targets for buffer widths around wetland boundaries based on the sensitivity and category of the wetland and the intensity of human activity proposed to be conducted. Table 2-5 provides these minimum regulatory buffer area requirements. Exemptions and exceptions to wetland protections and buffer widths can be found in MMC 22E.010

**TABLE 2-5
Wetland Buffer Widths**

Wetland Category	Buffer Width
Category I	125 feet
Ebey Slough	100 feet
Ebey Slough Exception: North and south shore between the western city limits, at approximately I-5, and 47 th Avenue NE	25 feet
Category II	100 feet
Category III	75 feet
Category IV	35 feet


AQUIFER RECHARGE AREAS

Marysville relies on an aquifer for potable drinking water only in the Lake Goodwin area. Surrounding aquifers within the City’s UGA mainly provide discharge into streams, supporting year round flow and crucial fish and wildlife habitat. The Marysville Trough Aquifer and the Getchell-Snohomish Aquifer are both partially located within the Marysville UGA and benefit from stream and wetland protections under the Critical Area Ordinance.

The Marysville Trough Aquifer and the Getchell-Snohomish Aquifer also have an influence on Geologic Hazard Areas and storm water runoff. In the winter months, the ground water levels in these aquifers often reach ground level causing overland flow that can carry pollutants directly into surface waters, and cause flooding in some areas. Additionally, the saturated soils create favorable conditions for landslides to occur in areas with steep slopes and can increase erosion, reducing the suitable habitat for salmon.

FISH AND WILDLIFE HABITAT AREAS

Most of the City’s wildlife habitat exists in areas that have retained second growth forest or heavy vegetation. This includes the healthy salmonid spawning and rearing habitat at the headwaters of many of the tributaries to Quilceda Creek and Allen Creek. Healthy Coho and Chum salmon spawning and rearing habitat can be found in many parts of the Quilceda Creek system along with resident cutthroat trout habitat in the headwaters of Edgecomb Creek. Fish habitat in agricultural areas has declined as buffers are not common in agricultural fields. Much of the spawning habitat has diminished in the Allen Creek system due to erosion causing stream beds to fill in with mud and silt, canary reed grass growing in streambeds/channelized sections of the system, and eliminated wetlands. Chinook salmon, steelhead, and rainbow trout also utilize the streams in the Quilceda and Allen Creek watersheds but to a lesser degree than the previously mentioned species.



Wetlands		Basin Name	
	Category 1		Allen Creek Basin
	Category 2		Ebey Slough Basin North
	Category 3		Ebey Slough Basin South
	Category 4		King Creek Basin
	Water Bodies		Quilceda Creek Basin
	Wetland Buffers		

Marysville City Limits
 Urban Growth Boundary
 Streams

Note: Wetlands shown are reflective of what information the City has obtained to date. This map is not comprehensive and is not intended to be used for site specific purposes.

0 5,000 10,000 15,000 Feet

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

WETLANDS MAP
FIGURE 2-6

In order to provide protection for crucial anadromous fish and other aquatic habitat, the City of Marysville has classified its stream system into four categories, per WAC 222-16-30.

The following categories are defined by MMC 22E.010.220 and are shown in Figure 2-7.

Type S Stream: Those streams, within their ordinary high water mark, as inventoried as “shorelines of the state” under Chapter 90.58 RCW and the rules promulgated pursuant thereto.

Type F Stream: Those stream segments within the ordinary high water mark that are not Type S streams, and which are demonstrated or provisionally presumed to be used by salmonid fish. Stream segments which have a width of two feet or greater at the ordinary high water mark and have a gradient of 16 percent or less for basins less than or equal to 50 acres in size, or have a gradient of 20 percent or less for basins greater than 50 acres in size, are provisionally presumed to be used by salmonid fish.

Type Np Stream: Those stream segments within the ordinary high water mark that are perennial and are not Type S or Type F streams. However, for the purpose of classification, Type Np streams include intermittent dry portions of the channel below the uppermost point of perennial flow.

Type Ns Stream: Those stream segments within the ordinary high water mark that are not Type S, Type F, or Type Np streams. These include seasonal streams in which surface flow is not present for at least some portion of a year of normal rainfall that are not located downstream from any Type Np stream segment.

Table 2-6 provides those categories along with their associated protected buffer widths.

TABLE 2-6

Stream Classifications and Buffer Width

Stream Category and Name	Description	Buffer Width
Type S	Shoreline	200 feet
	Quilceda Creek	100 feet
	Ebey Slough Except north and south shore between the western City limits and 47 th Avenue NE	25 feet
Type F	Fish bearing	150 feet
	Gissberg Twin Lakes	Lake setbacks correspond to county park boundaries
Type Np	Perennial	100 feet
Type Ns	Seasonal	50 feet

GEOLOGICALLY HAZARDOUS AREAS


Geologically hazardous areas are defined in the City's Municipal Code as lands or areas characterized by geologic, hydrologic, and topographic conditions that render them susceptible to potentially significant or severe risk of landslides, erosion, or seismic activity. Figure 2-8 is provided to give a general guide to where potential hazard areas are located within the City. Field investigation and analysis is required to confirm the presence or absence of these areas before development can occur. Generally, these areas warrant additional engineering investigation to assess the level of hazard and would typically require setbacks from these areas, special construction techniques, or outright prohibition with respect to land disturbance and development.

The most prominent Geological hazard area within the Marysville UGA is in the 100-year flood zone of Ebey Slough. This area is characterized to have moderate to high susceptibility to soil liquefaction during a seismic event. High susceptibility for soil liquefaction is also found along portions of Quilceda Creek and Allen Creek. Soil liquefaction may occur in areas that have saturated silt and/or sand soils when shaking due to seismic activity causes the soil to act as a liquid, losing its ability to support structures.

Landslide hazard areas have been identified in many areas of the Getchell Plateau including the banks along Munson Creek, and along the banks of Quilceda Creek and Allen Creek. A combination of steep slopes ranging from 25 percent to 75 percent, soft soils, and groundwater seepage create favorable conditions for landslides to occur. These areas, along with other tributaries to Quilceda and Allen Creeks, are also prone to erosion. The previously mentioned geologic conditions combined with human activities such as land use change/development have led to unstable slopes and increased stream flow, causing significant erosion in some areas.

STORMWATER UTILITY SERVICES

The City of Marysville has had a surface water management (SWM) program since 1991. Until 2007, the surface water utility fee was collected by Snohomish County in connection to property taxes and then remitted to the City of Marysville. In January 2007, the City's Public Works Department took over administration of the SWM utility and continues to manage the program. Fees collected by the SWM utility are for the purpose of operating public stormwater facilities to help reduce flooding and drainage problems, improve water quality, and meet regulatory requirements. Operation of this utility includes the ability to finance, construct, develop, improve, and maintain the City's stormwater facilities. The facilities consist of approximately 6,225 lineal feet of detention pipe, 185 miles of storm lines, 11,914 catch basins, 346 infiltration/detention ponds, and multiple outfalls into area receiving waters.



Stream Class	Basins	Other Features
S	Allan Creek Basin	Marysville City Limits
F	Ebey Slough Basin North	Urban Growth Boundary
NP	Ebey Slough Basin South	Streets
NS	King Creek Basin	Water Bodies
Unclassified	Quilceda Creek Basin	
	Stream Buffers	


Note: Stream classes shown have not been approved by the Wa. Dept. of Fish and Wildlife

0 5,000 10,000 15,000 Feet

2016 SURFACE WATER COMPREHENSIVE PLAN UPDATE

STREAM CLASSES MAPS

FIGURE 2-7



Percent Slope	Liquification Susceptibility	Symbol	Description
15 - 25%	High	—	Marysville City Limits
25 - 33%	Moderate to High	---	Urban Growth Boundary
33 - 40%	Flood Hazard	—	Streams
40 - 100%	Water Bodies	—	

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

GEOLOGIC HAZARD AREAS
FIGURE 2-8

CITY OF
Marysville
WASHINGTON

CHAPTER 3

STORMWATER MANAGEMENT SYSTEM ANALYSIS

INTRODUCTION

This chapter presents an analysis of the City of Marysville's existing stormwater management system, and its ability to accommodate flow for future development conditions. The analysis includes review of previous reports completed by Snohomish County and the City of Marysville, hydraulic and hydrologic modeling of areas identified by City staff, and feasibility studies for water quality improvements to address discharge into compromised waterways.

EXISTING STORMWATER MANAGEMENT SYSTEM

The City's existing stormwater management system consists of a combination of open ditches, pipes, catch basins, culverts, detention ponds, detention vaults, infiltration ponds, infiltration vaults, bioswales, filter strips, raingardens, and water quality treatment ponds. A base map showing drainage facilities within the City is shown in Figure 3-1. A large fold-out map is also included in Appendix A.

REFERENCED REPORTS

The following reports were reviewed during the analysis of the City's stormwater management system:

- *Quilceda Creek Drainage Needs Report, DNR No. 1, December 2002, Snohomish County Public Works Department Surface Water Management Division*
- *Allen Creek Drainage Needs Report, DNR No. 8, December 2002, Snohomish County Public Works Department Surface Water Management Division*
- *City of Marysville Surface Water Comprehensive Plan Update, February 2009, Otak, Inc.*
- *North Marysville Edgecomb Creek Relocation Feasibility Study, July 2009, Otak, Inc.*

WATER QUALITY

While water quality is an important part of stormwater management, this Plan focuses mostly on conveyance infrastructure. Marysville holds a Phase II National Pollutant Discharge Elimination System (NPDES) Stormwater Permit, which requires annual reporting of stormwater monitoring and assessment. Further information about

Marysville's water quality program may be found in the City of Marysville's Stormwater Management Program Plan (SWMP) available on the City's website.

CITY IDENTIFIED STORMWATER CONVEYANCE PROBLEMS

City employee comments and public complaints were reviewed in order to identify any issues that have occurred since the 2009 Surface Water Comprehensive Plan (2009 Comp Plan). A field investigation of specific problem areas was conducted to identify new projects. The City also provided an account of projects identified in previous plans that still need to be addressed. Many of these projects required reevaluation to ensure compliance with the Washington Department of Fish and Wildlife 2013 Water Crossing Guidelines (WDFW 2013 Guidelines) Modeling.


Hydrologic and hydraulic models of the City's stormwater system and drainage basins were developed by Snohomish County while conducting the 2002 Drainage Needs Report No. 1 for the Quilceda Creek Basin (2002 DNR No. 1) and the 2002 Drainage Needs Report No. 8 for the Allen Creek Basin (2002 DNR No. 8). Updated versions of the models were used in the 2009 Comp Plan, and additional modeling was performed for the current Plan.

HYDROLOGIC MODEL

Hydrologic analysis addresses the movement of rainfall to the conveyance system. The purpose of a hydrologic model is to predict the flow of stormwater runoff into the system. Hydrologic models were developed by Snohomish County for the 2002 DNRs using the Hydrologic Simulation Program- FORTRAN (HSPF), version 12.0, developed by the United States Environmental Protection Agency. The HSPF model simulates rainfall-runoff from pervious and impervious land surfaces, soil moisture dynamics, and hydrologic routing on a continuous basis, and uses historical rainfall records to generate a long-term series of stormwater discharges. The long-term flow record is necessary for the evaluation of detention facilities and other volume-dependent features within the conveyance system, and is important in the Puget Sound region for accurately evaluating flooding, where flooding is often caused by a series of back-to-back storm events rather than an isolated rainfall event.

HYDRAULIC MODEL


Hydraulic analysis addresses the movement of runoff through the conveyance system. The purpose of a hydraulic model is to evaluate the capacity of features within the conveyance system, such as pipes, culverts, and open channels. Hydraulic modeling for the stream systems and tributary open channels within the Marysville UGA was developed by Snohomish County for the 2002 DNRs using the Hydrologic Engineering Center River Analysis System (HEC-RAS) model. HEC-RAS is a backwater model designed to simulate the hydraulics of open channel systems, and can simulate flow through culverts and other features commonly found throughout a developed area.




Basin Name	Storm Facilities	Marysville City Limits
Allen Creek Basin	Detention Pond	Urban Growth Boundary
Ebey Slough Basin North	Infiltration Pond	Water Bodies
Ebey Slough Basin South	Stormlines	Streams
King Creek Basin		
Quilceda Creek Basin		

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

EXISTING STORMWATER FACILITIES
FIGURE 3-1





0 3,000 6,000 9,000 Feet

For a portion of the Sunnyside neighborhood within the Allen Creek Basin, a model was developed by Snohomish County using the Extran portion of the U.S. Environmental Protection Agency’s Stormwater Management Model (SWMM). For this model, storms were identified that had peak flows at or near the 2-year, 10-year, and 25-year return frequency peaks, and of these, three 3-day events were selected to account for antecedent rainfall. In the 2009 Comp Plan, a later and proprietary version of this same modeling software (XPSWMM, owned by XP Solutions) was used to simulate conveyance systems and detention ponds within the North Marysville region.

XP Solutions later developed a newer version of XPSWMM called XPStorm, which was used for this current Plan to model the designs for culverts subject to the WDFW 2013 Guidelines, and to evaluate flooding issues.

DRAINAGE BASINS

The City’s stormwater infrastructure is divided into four drainage basins: Quilceda Creek, Allen Creek, King Creek, and Ebey Slough. Table 3-1 shows the total area of each basin, as well as the area within the Marysville UGA. These basins are described in detail in Chapter 2.

TABLE 3-1

Drainage Basin Summary

Basin	Total Area (mi ²)	Area within UGA (mi ²)
Quilceda Creek	36.6	9.3
Allen Creek	10.4	7.7
King Creek	2.9	1.6
Ebey Slough	1.9	1.9

IDENTIFIED DEFICIENCIES

After review of deficiencies identified by the past Snohomish County Plans, staff comments and public complaints, the following areas have been identified as current deficiencies. These areas are named and organized by drainage basin, and described below. The two letters in the identification number of the problem area represent the initials of the drainage basin (e.g., QCI = Quilceda Creek Area No. 1). The former name of the projects from the 2009 Comp Plan is given in parentheses. The new identification numbers also correspond to the number assigned to the recommended Capital Improvement Plan (CIP) project for each individual project. Further discussion regarding solutions or recommended CIPs for these problem areas is described in Chapter 4 (Capital Improvement Plan).

QUILCEDA CREEK BASIN

Several key problem areas were identified within the Quilceda Creek Basin. These areas include flooding issues, fish passage barriers, ecological deficiencies, aging infrastructure, and stormwater management. Figures 3-2 and 3-3 locate the Quilceda Creek areas described herein.

QC1 Stormwater Pipe Damage at Edward Springs Reservoir

City staff identified a 36-inch CMP drainage pipe that runs along the northeast side of the Edward Springs Reservoir (SD-LINE-15039) as having significant rust damage due to age. The recommended solution for this issue is to replace 395 LF of CMP pipe with new corrugated polyethylene (CPEP) pipe.

QC2 (Formerly MQ-HH-19) Irrigation Ditch Accessible to Fish Upstream of 160th Street NE

Upstream of 160th Street NE, Hayho Creek and its tributaries are subject to water withdrawals for irrigation. Waterways used for irrigation require a fish screen downstream of the withdrawal to prevent fish from being drawn into the diversion channels. Installing a fish screen at this location will protect fish by blocking off approximately 1 mile of diversion channels to fish access. This was proposed in the 2009 Comp Plan, and originated from city staff recommendations.

QC3 (Formerly MQ-EC-03, MQ-EC-05) Undersized Field Access Culvert along Edgecomb Creek

Two privately owned undersized 30-inch field access culverts along Edgecomb Creek were identified by the 2002 DNR No.1 (IDs of SD-CV-167 and SD-CV-168). These were also identified as Level A barriers to fish passage. The HEC-RAS model developed for the previous report determined that the field access roads would be overtopped at the 2-year frequency for existing and future land use conditions. A reevaluation of these culverts was conducted for current fish passage standards. The results showed that these culverts are a velocity barrier for fish passage. The recommended solution for this issue is to replace both 30-inch culverts with two 16-foot span reinforced concrete box culverts. Culverts should be countersunk 30 percent and should be filled with gravel and sediment to comply with WDFW 2013 Guidelines.

QC4A (Formerly MQ-HH-16) Hayho Creek Channel Mitigation (North Marysville Master Drainage Plan)

The North Marysville Edgecomb Creek Relocation Feasibility Study was conducted in 2009 to investigate mitigating impacts of high-density development in the Smokey Point Region. The Hayho Creek drainage basin is one of two basins present in the study area, and was evaluated for improvements to allow for development while improving aquatic

resource function. Proposed improvements for this area include realigning the headwaters of Hayho Creek through existing wetlands.

QC4B (Formerly MQ-HH-32) Conveyance for Regional Detention Pond 2

The North Marysville Master Drainage Plan describes the need for installing what is currently known as Regional Pond 2 which was constructed in 2015. This pond, in conjunction with Pond 1 (built in 2004) allows for mitigation of impacts from high-density development in the Smokey Point Region. In general, Ponds 1 and 2 were designed to provide flow control and enhanced water quality treatment for 204.8 acres. Assumed land use north of the ponds includes commercial or light industrial development with 85 percent maximum impervious area. Of those 204 acres, 44.52 acres are anticipated to come from the west side of Smokey Pt. Blvd., north of 152nd Street NE. The remaining 160.31 acres would come from the east side of Smokey Pt. Blvd., north of 152nd Street NE and west of Hayho Creek. As part of the regional pond construction, 1,200 LF of 42-inch conveyance pipe and 191 LF of a 58-inch by 36-inch arched pipe was installed between the ponds and 152nd Street NE. However, additional conveyance will be necessary as development occurs within the collection basin for the regional ponds. Proposed conveyance for this area includes construction of 4,440 LF of 42-inch mainline conveyance pipe which will be used to serve future commercial or industrial areas.

QC4C (Formerly MQ-HH-32) Hayho Creek Regional Detention Pond 3

Regional Ponds 1 and 2 are intended to collect runoff west of Hayho Creek. Due to topography and the existence of Hayho Creek, it is infeasible to convey runoff east of Hayho Creek into the regional ponds. Therefore, a third regional pond is recommended to collect runoff from a small area east of Hayho creek, north of 152nd Street NE. With an estimated size of 3.5 acres, Regional Pond 3 is anticipated to be smaller than Ponds 1 and 2.

QC5A (Formerly MQ-EC-13) Edgecomb Creek Channel Mitigation (North Marysville Master Drainage Plan)

The North Marysville Edgecomb Creek Relocation Feasibility Study was conducted in 2009 to investigate impacts of high-density development in the Smokey Point Region. The development of this area would require the filling of remaining wetlands in the North Marysville Planning area, and the relocation of Edgecomb Creek. The study found that realigning Edgecomb Creek to the west side of the Burlington Northern Santa Fe Railroad would allow for improved function of the waterway and floodplain, while minimizing impacts to other waterways in the region. It would provide 64 acres of forested buffer along the realigned creek, create 29 acres of total wetland within the floodplain corridor, and provide adequate capacity within the constructed floodplain for the 100-year flood. This alignment requires minimal water crossings.

QC5B (Formerly MQ-EC-13) Edgecomb Creek Conveyance (North Marysville Master Drainage Plan)

In conjunction with realigning Edgecomb Creek, as development occurs, stormwater conveyance will be necessary to carry runoff away from developed sites located north of 152nd Street NE and east of 51st Avenue NE. To mitigate the need for onsite detention and treatment, a regional pond could be installed south of where the development is anticipated to occur (see QC5C below). The City could work with developers in providing a mainline conveyance trunk to this regional pond.

QC5C (Formerly MQ-EC-13) Edgecomb Creek Channel Mitigation (North Marysville Master Drainage Plan)

To mitigate the need for individual onsite detention and water quality treatment facilities, a 20-acre regional detention/treatment facility could be located at the south end of the Edgecomb study area, east of 51st Avenue NE and adjacent to the BNSF railway. It would serve commercial/industrial property located north of the pond and adjacent to or just east of 51st Avenue NE.

QC6 (Formerly MQ-EC-01) Undersized Culvert along Edgecomb Creek at 152nd Street NE

The 36-inch culvert conveying water beneath 152nd Street NE along Edgecomb Creek (SD-CV-147) was identified by the 2002 DNR No. 1 as undersized, and as a Level A barrier to fish passage. The HEC-RAS model developed for the previous report determined that 152nd Street would be overtopped at the 25-year frequency for existing land use conditions and the 10-year frequency for future land use conditions. A reevaluation of the culvert was conducted for current fish passage standards, where it was determined to be a velocity barrier for fish passage. The recommended solution for this issue is to replace the existing 36-inch culvert with a 17-foot span reinforced concrete box culvert. The culvert should be countersunk 30 percent and should be filled with gravel and sediment to comply with WDFW 2013 Guidelines.

QC7 (Formerly MQ-MQ-07) Undersized Culvert along Olaf Strad Creek at 152nd Street NE

The 36-inch culvert conveying water beneath 152nd Street NE along Olaf Strad Creek (SD-CV-31) was identified in the 2009 Comp Plan as undersized, and as a potential barrier to fish passage. A reevaluation of the culvert was conducted for current fish passage standards, where it was determined to be a velocity barrier for fish passage. The recommended solution for this issue is to replace the existing 36-inch culvert with a 15-foot span reinforced concrete box culvert. The culvert should be countersunk 30 percent and should be filled with gravel and sediment to comply with WDFW 2013 Guidelines.

QC8 (Formerly MQ-MQ-04) Undersized Culvert and Diminished Habitat along Quilceda Creek at Strawberry Fields Trail

The 36-inch culvert conveying water beneath the Strawberry Fields Trail along Middle Fork Quilceda Creek (SD-CV-3407) was identified by public complaints to have significant flooding issues. Additionally, it was identified in the 2002 DNR No. 1 to be a velocity barrier for fish passage. A reevaluation of the culvert was conducted for current fish passage standards, and was determined to be a velocity barrier for fish passage. Snohomish County also found the reaches of Middle Fork Quilceda Creek upstream and downstream of the culvert to have insufficient habitat. This was due to a lack of adequate large woody debris (LWD) and riparian recruitment. The recommended solution for this issue is to replace the existing 36-inch culvert with a 19-foot span reinforced concrete box culvert. The culvert should be countersunk 30 percent and should be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Native riparian vegetation and LWD should also be installed along 1,750 linear feet of the existing channel to improve fish habitat.

QC9 (Formerly MQ-HH-09) Flooding of 43rd Avenue and Emerald Hills Estates

The 2009 Comp Plan found that beaver dams in Hayho Creek cause periodic flooding of 43rd Avenue NE and the adjacent retirement community. The recommended solution for this problem is to install a berm on the downstream side of the 24-inch culvert beneath 43rd Avenue (SD-CV-52), and excavate the ditch on the northwest side of the berm to allow collection of street runoff and backwatering from Hayho Creek.

QC10 (Formerly MQ-HH-38) Channel Erosion on Hayho Creek between the Burlington Northern Santa Fe Railroad and 47th Drive NE

The 2009 Comp Plan found the reach of Hayho Creek between the Burlington Northern Santa Fe Railroad (BNSF) and 47th Drive NE to be incising and to have significant bank erosion. This is creating a backwater issue that is causing flooding of 136th Street NE at 45th Avenue. The recommended solution to this issue is to stabilize the reach by regrading 850 linear feet of channel. Additionally, large woody debris and native riparian vegetation should be installed along both streambanks.

QC10A Flooding of 136th Street NE at 45th Avenue NE

Significant flooding has been observed on the north side of 136th Street NE at 45th Avenue NE during intense or prolonged rain events. The flood water is generated from a ditch system that runs along 136th Street NE, but is thought to be due to a backwater issue in Haybo Creek on the east side of 45th Avenue NE. This backwater issue is created downstream in a reach located between the BNSF RR and 47th Drive NE that has diminished capacity due to erosion.

The ditch system along 136th Street NE, its confluence with Hayho Creek, and the downstream stretch of Hayho Creek between 136th and the BNSF RR were modeled in XPSTORM to examine alternatives for preventing the flooding on 136th Street NE. The model used the Santa Barbara Urban Hydrograph method (SBUH) to simulate runoff within the conveyance system. Basin areas were estimated to produce peak flows for the Type 1A storm that matched the flows reported for the 100-year storm event in the 2002 DNR No. 8. The model confirmed that the flooding was due to a backwater issue from Hayho Creek, and that approximately 51,000 cubic feet of runoff along the north side of 136th Street NE would need to be stored to prevent overtopping of the road if the downstream backwater issue caused south of the BNSF culverts was not resolved. The model also showed a capacity issue upstream where a 15-inch culvert between two sections of ditch along 136th Street NE has a reverse slope.

While fixing the downstream erosion issue within Hayho Creek is the optimum solution to this flooding problem, an alternative, more economical solution can be installed to prevent the flooding of 136th Street NE until funds are available to perform the necessary downstream repairs. The recommended alternative solution for this issue is to install a storage pond along 136th Street NE at 45th Avenue NE, regrade the section of ditch located approximately 450 feet west of 45th Avenue NE, and replace the 15-inch culvert just upstream from the regraded ditch. This would allow temporary storage of the runoff until the water level downstream recedes.

QC11 (Formerly WQ-WQ-08) Undersized Culvert along a Tributary to West Fork Quilceda Creek at 104th Street NE

The 4-foot box culvert conveying water beneath 104th Street NE along Lower West Fork Quilceda Creek (SD-CV-42) was identified in the 2009 Comp Plan as undersized, and as a potential barrier to fish passage. It was also noted that beaver dams just downstream from the culvert were contributing to flooding, and had caused the culvert to become clogged with silt. In 2010, emergency maintenance was conducted, which resulted in the beaver dams being removed, and the culvert being cleaned out. A 24-inch culvert was also installed above the ordinary high water mark to reduce flooding. A reevaluation of the culvert was conducted for current fish passage standards, and the existing configuration was determined to be a velocity barrier for fish passage. The recommended solution for this issue is to replace the existing 4-foot box culvert with a 50-foot prefabricated bridge along 104th Street to improve fish passage.

QC12 (Formerly WQ-WQ-09) Undersized Culvert along a Tributary to West Fork Quilceda Creek at 103rd Street NE

The 24-inch culvert conveying water beneath 103rd Street NE along Lower West Fork Quilceda Creek (SD-CV-43) was identified in the 2009 Comp Plan as undersized, and as a potential barrier to fish passage. A reevaluation of the culvert was conducted for current standards, where it was determined to be a velocity barrier for fish passage. The

recommended solution for this issue is to replace the existing 24-inch culvert with a 50-foot prefabricated bridge along 103rd Street to improve corridor and fish passage.


QC13 (Formerly MQ-QC-09) Undersized Culvert along Quilceda Creek at State Avenue

The two 6-foot box culverts conveying water beneath State Avenue NE along Quilceda Creek (SD-CV-30) were identified in the 2002 DNR No.1 to be a velocity barrier for fish passage. A reevaluation of the culvert was conducted for current standards, where it was determined to be a velocity barrier for fish passage. The recommended solution for this issue is to remove the existing culverts and install a 175-foot precast bridge along State Avenue to address corridor and fish passage concerns.


QC14 (Formerly MQ-QC-12) Undersized Culvert along Quilceda Creek at BNSF Railroad


The 6-foot box culvert conveying water beneath the Burlington Northern Santa Fe Railroad along Quilceda Creek (SD-CV-29) was identified in the 2002 DNR No. 1 to be a velocity barrier for fish passage. A reevaluation of the culvert was conducted for current standards, where it was determined to be a velocity barrier for fish passage. A possible solution for this issue is to remove the existing culvert and to install a 22-foot-diameter, 10-gauge tunnel liner plate. The tunnel liner plate provides a corrugated pipe with continuous circumferential corrugations which provide high strength and stiffness. The tunnel should be countersunk 30 percent and should be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Although this issue is within the Marysville city limits, it is within BNSF right-of-way; and therefore, it is the responsibility of BNSF to replace this culvert.

Page Intentionally Left Blank



<p>QC1: Stormwater Pipe Damage at Edward Springs Reservoir Issue: Damage Potential Solution: Replace 395 LF of 36" CMP pipe with 36" CPEP pipe</p> <p>QC2: Irrigation Ditch Accessible to Fish upstream of 160th St NE Issue: Biological Potential Solution: Install fish screen</p> <p>QC3: Undersized Field Access Culverts Issue: Capacity/ Fish Passage Potential Solution: Replace existing culverts with 16'x6' concrete box culverts</p> <p>QC4A: Hayho Creek Channel Mitigation (North Marysville Master Drainage Plan) Issue: Mitigation/Habitat Potential Solution: Realign headwaters of Hayho Creek</p> <p>QC4B: Conveyance for Regional Detention Pond No.2 Issue: Mitigation Potential Solution: Install 4,400 LF 42-inch conveyance pipe</p> <p>QC4C: Hayho Creek Regional Detention Pond No.3 Issue: Mitigation Potential Solution: Install 3.5 ac regional detention pond.</p> <p>QC5A: Edgecomb Creek Channel Mitigation (North Marysville Master Drainage Plan) Issue: Mitigation/Habitat Potential Solution: Realign 2 miles of Edgecomb Creek</p> <p>QC5B: Edgecomb Creek Conveyance Issue: Mitigation Potential Solution: Install 10,550 LF conveyance pipe (25" - 54")</p>	<p>QC5C: Edgecomb Creek Regional Detention Facility Issue: Mitigation Potential Potential Solution: Install 20ac regional detention pond</p> <p>QC6: Undersized Culvert at 152nd St NE Issue: Capacity/ Fish Passage Potential Solution: Replace existing culvert with a 17'x6' concrete box culvert</p> <p>QC7: Undersized Culvert at 152nd St NE Issue: Capacity/ Fish Passage Potential Solution: Replace existing culvert with a 15'x5' concrete box culvert</p> <p>QC8: Undersized Culvert and Diminished Habitat at Strawberry Fields Trail Issue: Capacity/ Fish Passage/ Habitat Potential Solution: Replace existing culvert with a 19'x7' concrete box culvert and install native riparian vegetation along 1,750 LF of channel</p> <p>QC9: Flooding of 43rd Ave at Emerald Hills Estates Issue: Capacity/Biological Potential Solution: Install berm and excavate ditch</p> <p>QC10: Channel Erosion on Hayho Creek between BNSF and 47th Dr NE Issue: Capacity/ Habitat Potential Solution: Regrade 850 LF of Creek and install native riparian vegetation</p> <p>QC10-A: Flooding of 136th St NE Issue: Capacity Potential Solution: install storage pond along 136th St NE and replace reverse slope culvert</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------





	Identified Deficiency		Streams
	Allen Creek Basin		BNSF Railroad
	Ebey Slough Basin North		Marysville City Limits
	Quilceda Creek Basin		Urban Growth Boundary
	Water Bodies		

2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE
 IDENTIFIED DEFICIENCIES
 QUILCEDA CREEK BASIN SOUTH
 FIGURE 3-3

ALLEN CREEK BASIN

Deficiencies found in the Allen Creek Basin primarily involve flooding due to undersized storm pipes. One other issue was identified involving a culvert that was found to have structural issues and is a barrier to fish. Figure 3-4 locates the Allen Creek areas described herein.

AC1 (Formerly AC-AC-10) Undersized Stormwater Pipes at 95th Street NE and 67th Avenue NE

The storm pipe system along 95th Street NE between 95th Place NE and 67th Avenue NE was found to have insufficient conveyance capacity by Snohomish County in the 2002 DNR No. 8. The HEC-RAS model generated for the previous report determined that flooding would occur during the 10-year event for existing and future land use. The recommended solution for this issue is to replace 227 linear feet of existing 12-inch-diameter storm pipe with 18-inch-diameter HDPE pipe.

AC2 (Formerly AC-AC-03) Undersized Culvert and Erosion of the Stream Bank Along Allen Creek at 88th Street NE

The 7-foot box culvert conveying water beneath 88th Street NE along Allen Creek (SD-CV-23) was identified in the 2002 DNR No. 8 as undersized, and as a velocity barrier to fish passage. A reevaluation of the culvert was conducted for current fish passage standards, where it was confirmed to be a velocity barrier for fish passage.

Structural and maintenance issues were also found at this culvert. The survey crew reported the upstream section of the culvert had separated from the rest of the culvert, and a hydraulic jump is predicted at the 2-year event or less. No jump is predicted for higher flows. In addition, a 50-foot section of riprap-armored stream bank has failed. Roadway overtopping is predicted if the culvert is not maintained.

The recommended solution for this issue is to replace the existing 7-foot span culvert with a 25-foot span reinforced concrete box culvert. Loose rip rap from the channel should be removed and 50 linear feet of bioengineered bank stabilization measures should be installed along the eroded south bank.


AC3 (Formerly AC-JC-12) Undersized Stormwater Pipes at 61st Street NE Cul-de-Sac

The storm drain system along the 61st Street NE Cul-de-Sac was identified in the 2009 Comp Plan to have insufficient conveyance capacity. The XP-SWMM model developed for this report shows flooding will occur at the 10-year event for existing land use conditions. Since the 2009 Comp Plan, a stream restoration and capacity improvement project was completed along Jones Creek, potentially reducing the severity of this conveyance issue. The Jones Creek portion of the 2002 DNR No. 8 HEC-RAS model

should be updated to include these improvements, and a new hydraulic analysis should be conducted to determine the remaining flooding issues. The recommended solution for this issue is to replace approximately 580 linear feet of existing 12-inch pipe with 420 linear feet of 15-inch CPEP pipe and 160 linear feet of new 12-inch-diameter CPEP pipe. The five catch basins along this drainage line should be replaced with 48-inch, Type II catch basins.

AC4 (Formerly AC-JC-II) Undersized Stormwater Pipes at 60th Place NE and the Surrounding Area

The storm drain system along 60th Place NE, 64th Avenue NE, and 63rd Avenue NE was identified in the 2009 Comp Plan to have insufficient conveyance capacity. The XP-SWMM model developed for this report shows flooding will occur at the 10-year event for existing land use conditions. Since the 2009 Comp Plan, a stream restoration and capacity improvement project was completed along Jones Creek, potentially reducing the severity of this conveyance issue. The Jones Creek portion of the 2002 DNR No. 8 HEC-RAS model should be updated to include these improvements, and a new hydraulic analysis should be conducted to determine the remaining flooding issues. The recommended solution for this issue is to replace approximately 1,230 linear feet of existing 12-inch storm pipe with 450 linear feet of 18-inch-diameter CPEP pipe and 780 linear feet of 15-inch-diameter CPEP pipe. The 13 catch basins within the project area should be replaced with 48-inch, Type II catch basins.



	Identified Deficiency		Streams
	Allen Creek		Marysville City Limits
	King Creek		Urban Growth Boundary
	Quilceda Creek		
	Water Bodies		

0 2,000 4,000 6,000 Feet

2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE
**IDENTIFIED DEFICIENCIES
 ALLEN CREEK BASIN**
 FIGURE 3-4

EBEY SLOUGH NORTH BASIN

Two areas were identified within the Ebey Slough North Basin as needing a detailed analysis and design of both site-specific and end-of-pipe solutions to improve stormwater quality and quantity before its discharges into Ebey Slough. Figure 3-5 locates the Ebey Slough Basin areas described herein.


ES1 Historic Downtown Green Retrofit Study

The City of Marysville would like to provide water quality treatment to stormwater runoff that is generated within its Historic Downtown District. The downtown area discharges untreated runoff from the right of way directly into Ebey Slough, an impaired waterway and a tributary of the Snohomish River. This study will start by creating criteria for the selection of ideal areas within Historic Downtown Marysville to carry forward into the design phase. The design phase will focus on using the 2014 Department of Ecology Stormwater Management Manual for Western Washington and the 2012 Low Impact Development Technical Guidance Manual for Puget Sound to implement green infrastructure principles that mimic predeveloped hydrologic conditions for the specific project areas. These mitigation techniques may include infiltration, filtration, and transpiration to improve water quality and quantity.


ES2 (Formerly ES-DT-03) Water Quality at Downtown Marina Outfall Study

A study of the Downtown region should be conducted to identify alternatives and provide a design of an end-of-pipe stormwater treatment facility to accompany the water quality improvements to the 480-acre basin located upstream of the Marina area. While reductions to basin flows and creating localized treatment through LID retrofits is effective and important, significant areas of the large, older developed basin remain untreated. Creating a regional treatment facility within the system will allow for treatment of any remaining basin runoff that is not currently being addressed by treatment facilities installed to date.

Page Intentionally Left Blank



- ▲ Identified Deficiency
- Allen Creek Basin
- Ebey Slough Basin North
- Quilceda Creek Basin
- Water Bodies
- Streams
- BNSF Railroad
- Marysville City Limits
- Urban Growth Boundary



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

**IDENTIFIED DEFICIENCIES
EBEY SLOUGH BASIN NORTH**

FIGURE 3-5

KING CREEK BASIN

One area was identified within the King Creek Basin to be a fish passage barrier, and to have insufficient culvert sizing to allow flood debris to pass through the system. Figure 3-6 locates the King Creek Basin area described below.

KC1 Undersized Culvert Along King Creek at Soper Hill Road

City staff identified significant debris buildup at the upstream opening of the 4-foot box culvert beneath Soper Hill Road along King Creek (SD-CV-157). The debris is thought to be the result of significant flooding in 2010. The culvert was also analyzed for fish passage and was determined to be a Level A barrier. The recommended solution for this issue is to replace the existing 4-foot box culvert with a 16-foot-long, 17-foot span, 7-foot rise reinforced concrete box culvert. The culvert should be countersunk 30 percent and the stream bed inside of the culvert should be constructed using a cascade-step or pool-riffle construction to comply with WDFW 2013 Guidelines.

Page Intentionally Left Blank

CHAPTER 4

CAPITAL IMPROVEMENT PLAN

INTRODUCTION

The City of Marysville's Stormwater Capital Improvement Plan is presented in this chapter of the 2016 Surface Water Comprehensive Plan Update. The recommended projects include structural and nonstructural elements to control both the quantity and quality of stormwater runoff, and to comply with the Washington State Department of Fish and Wildlife 2013 Water Crossing Guidelines.

The Capital Improvement Plan (CIP) was developed based on input from several sources. Sources included City staff, who identified storm drainage problems, the City's 2009 Surface Water Comprehensive Plan (2009 Comp Plan), and Snohomish County's 2002 Drainage Needs Report No. 1 and No. 8 for the Quilceda Creek Basin and the Allen Creek Basin respectively (2002 DNR No. 1 and 2002 DNR No. 8), which were both reviewed for projects completed and projects outstanding.

Whenever an inadequately sized culvert, pipe, or channel is replaced or reconstructed, the improvement may transfer the problem downstream. It is therefore strongly recommended that all improvements include analysis of downstream conditions. As a general rule, projects should proceed from the downstream end of the system towards the upstream end of the system.



Other stormwater capital improvement projects may arise in the future that are not identified as part of the City's CIP presented in this chapter. Such projects may be deemed necessary for remedying an emergency situation, assessing growth in other areas, accommodating improvements proposed by other agencies or land development, or addressing unforeseen problems with the City's storm drainage system. Due to budgetary constraints and/or addressing growth scenarios that differ from those modeled in this Plan, the construction of these projects may require changes in the proposed completion date for projects in the CIP. When new information becomes available, the City retains the flexibility to reschedule, add to, or delete proposed projects and to expand or reduce the scope of the projects, as best determined by the City. Each capital improvement project should be re-evaluated to consider the most recent relevant planning efforts as the proposed project date approaches.

CAPITAL IMPROVEMENT PROJECTS

This Surface Water Comprehensive Plan Update reviewed the outstanding projects from the 2009 Comp Plan. In the 2009 Comp Plan, there were 30 capital improvement projects (CIPs) identified. Of those 30 CIPs, four have been completed or have been resolved by the completion of other projects as of Summer 2016. Interviews with City

staff revealed four additional CIPs including a culvert replacement in the King Creek Basin (KC1), a pipe replacement west of the Quilceda Creek Basin (QC1), flood storage at 136th Street NE (QC10-A), and a feasibility/design study for green retrofit projects in the Historic Downtown area (ES1).

The recommended CIP projects scheduled for completion within future years are summarized below and are shown in Figure 4-1. Each project cost estimate includes an additional 20 percent construction contingency, 25 percent for design, engineering, and permitting, and a 9.1 percent sales tax. All project costs are based on 2016 dollars with no adjustments made for inflation in future years. The naming convention uses the initials of the drainage basin that the projects fall within, along with an identification number. It should be noted that many of the projects listed may take lengthy coordination with other agencies for permitting purposes. Permit acquisition should be considered within the project's overall schedule.



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

**CIP PROJECTS
FIGURE 4-1**

QUILCEDA CREEK BASIN PROJECTS

QC1: Stormwater Pipe Replacement at Edward Springs Reservoir

Replace 395 linear feet of 36-inch-diameter CMP pipe with 395 linear feet of CPEP pipe. Connect to the existing Type 2 catch basins on upstream and downstream ends of the pipe. Additional inspection of upstream and downstream pipe is recommended to determine whether additional replacement is required. The project is located just north of 172nd Street NW at the Edward Springs Reservoir (Figure 4-2).

Estimated Project Cost: \$381,000

QC2: Fish Screen Installation Along Hayho Creek at 160th Street NE

Install a fish screen along Hayho Creek upstream of 160th Avenue NE to prevent fish from being drawn into the diversion channel. Temporary bypass of flow around the work area will be necessary during construction. A biological assessment will be required prior to installation to determine the channel's suitability for fish (Figure 4-3).

Estimated Project Cost: \$231,000

QC3: Field Access Culvert Replacement along Edgecomb Creek

Replace both 30-inch culverts with 16-foot span, 6-foot rise reinforced concrete box culverts. The culverts shall be countersunk 30 percent and the streambed within the culverts shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Temporary bypass of flow around the work area will be necessary during construction. Coordination with the property owners will be necessary for this project as these culverts are privately owned (Figure 4-4).

Estimated Project Cost: \$617,000

QC4A: Hayho Creek Channel Realignment (North Marysville Master Drainage Plan)

Realign the headwaters of Hayho Creek through 15 acres of existing wetlands just south of the City limits, and install native wetland vegetation (Figure 4-5).

Estimated Project Cost: \$1,680,000

QC4B: Conveyance for Regional Detention Pond 2 (North Marysville Master Drainage Plan)

Provide approximately 4,400 LF of 42-inch conveyance pipe north of 152nd Street NE for the purpose of providing a main trunkline for future commercial or industrial development north of Regional Ponds 1 and 2 (Figure 4-5).

Estimated Project Cost: \$4,901,000

QC4C: Hayho Creek Regional Detention Pond 3

Construct a 3.5-acre regional detention pond at the northeast corner of 152nd Street NE and 43rd Avenue NE to detain and treat flow east of Hayho Creek that cannot reach Regional Ponds 1 or 2 (Figure 4-5).

Estimated Project Cost: \$1,831,000

QC5A: Edgecomb Creek Channel Realignment (North Marysville Master Drainage Plan)

Realign approximately two miles of Edgecomb Creek between 154th Drive NE and 172nd Street NE. This project includes installing 64 acres of forested buffer and 29 acres of wetland with native wetland vegetation. Install five fish passable culverts, two under the Burlington Northern Santa Fe Railroad, two railroad access road culverts, and one culvert under 152nd Street NE. Early permit coordination with Burlington Northern is encouraged prior to beginning a full design for the project (Figure 4-6).

Estimated Project Cost: \$19,042,000

QC5B: Edgecomb Creek Conveyance (North Marysville Master Drainage Plan)

Conveyance to the regional detention pond (Project QC5C) will require the installation of approximately 2,100 linear feet of 24-inch pipe, 1,300 linear feet of 30-inch pipe, 3,250 linear feet of 36-inch-diameter pipe, 1,300 linear feet of 42-inch pipe, and 2,600 linear feet of 54-inch-diameter pipe. The project will also require the installation of approximately 33 manholes ranging in size from 48 inch to 84 inch (Figure 4-6).

Estimated Project Cost: \$8,517,000

QC5C: Edgecomb Creek Regional Detention Facility (North Marysville Master Drainage Plan)

Construct a 20-acre regional detention pond at the south end of the project area between 51st Avenue NE and the Burlington Northern Santa Fe Railroad (Figure 4-6).

Estimated Project Cost: \$5,054,000

QC6: Culvert Replacement along Edgecomb Creek at 152nd Street NE

Replace the existing 36-inch culvert with a 17-foot span, 6-foot rise reinforced concrete box culvert. The culvert shall be countersunk 30 percent and the streambed within the culvert shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-7).

Estimated Project Cost: \$489,000

QC7: Culvert Replacement along Olaf Strad Creek at 152nd Street NE

Replace the existing 36-inch culvert with a 15-foot span, 5-foot rise reinforced concrete box culvert. The culvert shall be countersunk 30 percent and the streambed within the culvert shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-8).

Estimated Project Cost: \$520,000

QC8: Culvert Replacement and Channel Restoration along Middle Fork Quilceda Creek at Strawberry Fields Trail

Replace the existing 36-inch culvert with a 19-foot span, 7-foot rise reinforced concrete box culvert. The culvert shall be countersunk 30 percent and the streambed within the culvert shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Install native riparian vegetation and large woody debris (LWD) along 1,750 linear feet of existing channel. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-9).

Estimated Project Cost: \$548,000

QC9: Berm Installation at 43rd Avenue and Emerald Hills Estates

Install a berm on the downstream side of the 24-inch culvert under 43rd Avenue, and excavate the ditch on the northwest side of the berm to allow temporary storage of street runoff and backwatering from Hayho Creek during periods of active beaver dams (Figure 4-10).

Estimated Project Cost: \$69,000

QC10: Stabilization of Hayho Creek between the BNSF Railroad and 47th Drive NE

Stabilize 850 linear feet of Hayho Creek by regrading and installing LWD and riparian vegetation along streambank. Biological assessment of the stream and riparian corridor is necessary (Figure 4-11).

Estimated Project Cost: \$2,882,000

QC10A: Runoff Storage Along 136th Street NE at 45th Avenue

Install a stormwater storage pond along 136th Street NE, just west of 45th Avenue NE. Regrade a portion of the ditch upstream from the pond site and replace 145 linear feet of 15-inch HDPE pipe upstream of the ditch excavation with 145 linear feet of 18-inch CPEP pipe (Figure 4-11).

Estimated Project Cost: \$425,000

QC11: Culvert Removal and Bridge Installation at 104th Street NE

Replace the existing 4-foot box culvert with a 50-foot prefabricated bridge. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-12).

Estimated Project Cost: \$1,017,000

QC12: Culvert Removal and Bridge Installation at 103rd Street NE

Replace the existing 24-inch culvert with a 50-foot prefabricated bridge. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-13).



Estimated Project Cost: \$980,000

QC13: Culvert Removal and Bridge Installation Along Quilceda Creek at State Avenue

Remove both existing 6-foot span, 6-foot rise concrete box culverts and install a 180-foot prefabricated bridge along State Avenue. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-14).

Estimated Project Cost: \$6,755,000

Page Intentionally Left Blank



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC1)
FIGURE 4-2



QC2: Fish Screen Installation along Hayho Creek at 160th St NE
 Install fish screen along Hayho Creek
 Cost: \$231,000
 Priority: Low

QC4B

QC4C


QC9

- Stormlines**
- < 8 inch
 - 8 - 12 inch
 - 13 - 18 inch
 - 21 - 28 inch
 - 30 - 36 inch
 - > 42 inch
 - Storm Facilities

- Catch Basin**
- CB Type 1
 - CB Type 2
 - CB Type 3
 - CIP Project
 - Culvert
 - Streams




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE
CIP PROJECTS (QC2)
 FIGURE 4-3




QC3: Field Access Culvert Replacement along Edgecomb Creek
 Replace two 30" culverts with 16'x6' concrete box culverts
 Cost: \$617,000
 Priority: Low

- | | | | |
|-------------------|--------------------|--------------------|-------------------------------|
| Stormlines | Catch Basin | CIP Project | Marysville City Limits |
| — < 8 inch | • Cleanout | — Culvert | — Urban Growth Boundary |
| | • CB Type 1 | — Streams | — BNSF Railroad |
| | • CB Type 2 | | |



2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

**CIP PROJECTS (QC3)
 FIGURE 4-4**




QC4A: Hayho Creek Channel Realignment
 Realign headwaters of Hayho Creek
 Cost: \$1,680,000
 Priority: High

QC4B: Conveyance for Regional Detention Pond No. 2
 Install 4,400 LF of 42-inch conveyance pipe
 Cost: \$4,901,000
 Priority: High


QC4C: Hayho Creek Regional Detention Pond No. 3
 Install 3.5 acre regional detention pond
 Cost: \$1,831,000
 Priority: Medium

QC5A

QC5C





Stormlines	Catch Basin	CIP Project
< 8 inch	Cleanout	CIP Project
8 - 12 inch	CB Type 1	Streams
13 - 18 inch	CB Type 2	BNSF Railroad
21 - 28 inch	CB Type 3	Marysville City Limits
30 - 36 inch	Storm Facilities	Urban Growth Boundary
> 42 inch		



2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC4)
 FIGURE 4-5







QC6: Culvert Replacement along Edgecomb Creek at 162nd St NE
 Replace 36" culvert with 17x6' concrete box culvert
 Cost: \$489,000
 Priority: Medium

QC7

QC8




- | | | |
|-------------------|--------------------|--------------------------|
| Stormlines | Catch Basin | CIP Project |
| — < 8 inch | • CLEANOUT | — Culvert |
| — 8 - 12 inch | • CB Type 1 | — BNSF Railroad |
| — 13 - 16 inch | • CB Type 2 | — Marysville City Limits |
| — 21 - 28 INCH | • CB TYPE 3 | ■ Urban Growth Boundary |
| — 30 - 36 INCH | | |
| — > 42 INCH | | |



2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE


CIP PROJECTS (QC6)
FIGURE 4-7




QC7: Culvert Replacement along Olaf Strad Creek at 152nd St NE
 Replace 36" culvert with 15'x5' concrete box culvert
 Cost: \$520,000
 Priority: Medium

QC6

QC8





- | | | |
|-------------------|--------------------|--------------------------|
| Stormlines | Catch Basin | CIP Project |
| — < 8 inch | • CLEANOUT | — Culvert |
| — 8 - 12 inch | • CB Type 1 | — BNSF Railroad |
| — 13 - 18 inch | • CB Type 2 | — Marysville City Limits |
| — 21 - 28 INCH | • CB TYPE 3 | — Urban Growth Boundary |
| — 30 - 36 INCH | | |
| — > 42 INCH | | |




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC7)
FIGURE 4-8




Stormlines	Catch Basin	CIP Project
— < 8 inch	• CLEANOUT	— Culvert
— 8 - 12 inch	• CB Type 1	— BNSF Railroad
— 13 - 18 inch	• CB Type 2	— Marysville City Limits
— 21 - 28 INCH	• CB TYPE 3	— Urban Growth Boundary
— 30 - 36 INCH		
— > 42 INCH		



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE


CIP PROJECTS (QC8)
FIGURE 4-9




Stormlines	— 21 - 28 inch	Catch Basin	— Culvert
— < 8 inch	— 30 - 36 inch	• CB Type 1	— Streams
— 8 - 12 inch	— > 42 inch	• CB Type 2	
— 13 - 18 inch	■ Storm Facilities	• CB Type 3	
		● CIP Project	

2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATES


CIP PROJECTS (QC9)
FIGURE 4-10





QC10A: Runoff Storage along 136th Ave. NE at 45th Ave.
 Install a stormwater storage pond to accommodate 51,000 CF of runoff, replace 145 LF of 15" HDPE pipe with 145 LF of new 18" CPEP pipe, and regrade 75 LF of ditch downstream of the replaced pipe.
Cost: \$425,000
Priority: Medium


QC10: Stabilization of Hayho Creek between BNSF RR and 47th Dr. NE
 Regrade Hayho Creek, install LWD and riparian vegetation
Cost: \$2,882,000
Priority: Medium



- | | | |
|-------------------|--------------------|--------------------|
| Stormlines | Catch Basin | CIP Project |
| — < 8 inch | • CLEANOUT | — Culvert |
| — 8 - 12 inch | • CB Type 1 | — Streams |
| — 13 - 18 inch | • CB Type 2 | — BNSF Railroad |
| — 21 - 28 inch | • CB Type 3 | |
| — 30 - 36 inch | | |
| — > 42 inch | | |



2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE
CIP PROJECTS (QC10, QC10A)
FIGURE 4-11



- | | | | |
|-------------------|--------------------|--------------------|----------------------|
| Stormlines | Catch Basin | CIP Project | BNSF Railroad |
| — < 8 inch | ■ CB Type 1 | — Culvert | — Streams |
| — 8 - 12 inch | ● CB Type 2 | ■ Water Bodies | |
| — 13 - 18 inch | ■ Storm Facilities | | |


2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC11)
FIGURE 4-12





QC12: Culvert Removal and Bridge Installation at 103rd St NE
 Replace 24" concrete culvert with a 50' prefabricated bridge
 Cost: \$980,000
 Priority: Medium



- | | | | |
|-------------------|--------------------|--------------------|----------------------|
| Stormlines | Catch Basin | CIP Project | BNSF Railroad |
| — < 8 inch | ■ CB Type 1 | --- Culvert | — Streams |
| — 8 - 12 inch | ● CB Type 2 | ■ Water Bodies | |
| — 13 - 18 inch | ■ Storm Facilities | | |




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC12)
FIGURE 4-13



QC13: Culvert Removal and Bridge Installation along Quilceda Creek at State Ave
 Remove existing 6' box culverts and install a 180' prefabricated bridge
 Cost: \$6,755,000
 Priority: High



- | | | | |
|-------------------|--------------------|--------------------|----------------------|
| Stormlines | Catch Basin | CIP Project | BNSF Railroad |
| — < 8 inch | ■ CB Type 1 | --- Culvert | — Streams |
| — 8 - 12 inch | ● CB Type 2 | ■ Water Bodies | |
| — 13 - 18 inch | ■ Storm Facilities | | |

0 400 600 Feet
 Item 12-88

2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (QC13)
FIGURE 4-14

M:\MARYSVILLE\15150 00 Surface Water Comp Plan\GIS\Maps For Print\Figure 4-14.mxd

ALLEN CREEK BASIN

AC1: Storm Pipe Replacement at 95th Street NE and 67th Avenue NE

Replace 227 linear feet of existing 12-inch-diameter storm pipe with 18-inch-diameter CPEP pipe. Replace one 48-inch Type 2 catch basin (Figure 4-15).

Estimated Project Cost: \$161,000

AC2: Culvert Replacement and Erosion Control Measures at 88th Street NE

Replace the existing 7-foot span, 5-foot rise box culvert with a 25-foot span 10-foot rise reinforced concrete box culvert. The culvert shall be countersunk 30 percent and the streambed within the culvert shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. Remove loose rip rap from the channel and install 50 linear feet of bioengineered bank stabilization measures along the eroded south bank. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-16).

Estimated Project Cost: \$898,000

AC3: Storm Pipe Replacement at 61st Street NE Cul-de-Sac

Replace approximately 580 linear feet of existing 12-inch pipe with 420 linear feet of 15-inch CPEP pipe and 160 linear feet of new 12-inch-diameter CPEP pipe. Replace five 48-inch Type 2 catch basins (Figure 4-17).


Estimated Project Cost: \$323,000

AC4: Storm Pipe Replacement at 60th Place NE and Surrounding Area

Replace approximately 1,230 linear feet of existing 12-inch storm pipe with 450 linear feet of 18-inch-diameter CPEP pipe and 780 linear feet of 15-inch-diameter CPEP pipe. Replace 13 48-inch Type 2 catch basins (Figure 4-18).

Estimated Project Cost: \$654,000


Page Intentionally Left Blank



AC1: Storm Pipe Replacement at 95th St NE and 67th Ave NE
 Replace 227 LF of 12" pipe with 18" pipe
 Cost: \$161,000
 Priority: Low

AC2

- | | | |
|-------------------|--------------------|-------------------------------|
| Stormlines | Catch Basin | Marysville City Limits |
| — < 8 inch | ■ CB Type 1 | — Marysville City Limits |
| — 8 - 12 inch | ● CB Type 2 | ▬ Urban Growth Boundary |
| — 13 - 18 inch | ■ Storm Facilities | |
| — 21 - 28 inch | ■ CIP Project | |
| — 30 - 38 inch | — Culvert | |
| — > 42 inch | — Streams | |




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATES

CIP PROJECTS (AC1)
 FIGURE 4-15




AC2: Culvert Replacement and Erosion Control Measures at 88th St NE
 Replace 7'x5' box culvert with a 25'x10' box culvert and install 50 LF of bank stabilization
 Cost: \$695,000
 Priority: High

- | | | |
|-------------------|--------------------|-------------------------------|
| Stormlines | Catch Basin | Marysville City Limits |
| — < 8 inch | ■ CB Type 1 | — Marysville City Limits |
| — 8 - 12 inch | ● CB Type 2 | ■ Urban Growth Boundary |
| — 13 - 18 inch | ■ Storm Facilities | |
| — 21 - 28 inch | ■ CIP Project | |
| — 30 - 36 inch | — Culvert | |
| — > 42 inch | — Streams | |




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (AC2)
 FIGURE 4-16



AC3: Storm Pipe Replacement at 61st St NE Cul-de-sac
 Replace 580 LF of 12" pipe with 420 LF of 15" pipe and 160 LF of 12" pipe
 Cost: \$323,000
 Priority: Low

AC4




- | | | |
|-------------------|--------------------|--------------------|
| Stormlines | Catch Basin | CIP Project |
| — < 8 inch | • Cleanout | — Culvert |
| — 8 - 12 inch | ■ CB Type 1 | — Parcels |
| — 13 - 18 inch | • CB Type 2 | — Streams |
| — 30 - 36 inch | ■ Storm Facilities | |

2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (AC3)
FIGURE 4-17


0 200 400 600 Feet

Item 12-93



AC3

AC4: Storm Pipe Replacement at 60th Pl NE and surrounding area
 Replace 1,230 LF of 12" pipe with 450 LF of 18" pipe and 780 LF of 15" pipe
 Cost: \$554,000
 Priority: Medium



- | | | |
|-------------------|--------------------|--------------------|
| Stormlines | Catch Basin | CIP Project |
| < 8 inch | Cleanout | Culvert |
| 8 - 12 inch | CB Type 1 | Parcels |
| 13 - 18 inch | CB Type 2 | Streams |
| 30 - 36 inch | Storm Facilities | |

2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (AC4)
 FIGURE 4-18

Item 12-294

EBEY SLOUGH NORTH BASIN

ES1: Historic Downtown Green Retrofit Study

Create selection criteria to identify ideal locations for green stormwater infrastructure within the Historic Downtown District. Design stormwater management solutions in accordance with the 2012 *Low Impact Development Technical Guidance Manual for Puget Sound* and the 2014 Department of Ecology *Stormwater Management Manual for Western Washington* for the locations selected (Figure 4-19).


Estimated Project Cost: \$150,000

ES2: Water Quality Treatment Facility at Downtown Marina Outfall

Identify alternatives, design and construct an end-of-pipe stormwater treatment facility at the Downtown Marina outfall. The facility is estimated to be up to 12,000 sf and would provide treatment to the upstream downtown core of the City. The specific form of treatment will be identified in the predesign stage as numerous proprietary and standard facilities continue to be made available. For the purposes of this Plan, it is estimated that a new treatment facility will cost approximately \$350 per acre of facility provided (Figure 4-20).

Estimated Project Cost: \$8,208,000

Page Intentionally Left Blank



ES1: Historic Downtown Green Retrofit Study
 identify locations for and create design of LID
 facilities within the downtown core
 Cost: \$150,000
 Priority: High

ES2

Stormlines


- < 8 inch
- 8 - 12 inch
- 13 - 18 inch
- 21 - 28 inch
- 30 - 36 inch
- > 42 inch

Catch Basin

- CB Type 1
- CB Type 2
- CB Type 3
- Storm Facilities


CIP Project

- CIP Project
- Culvert
- Marysville City Limits
- BNSF Railroad
- Streams




2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (ES1)
 FIGURE 4-19



Stormlines	Catch Basin	CIP Project
< 8 inch	CB Type 1	CIP Project
8 - 12 inch	CB Type 2	Culvert
13 - 18 inch	CB Type 3	Marysville City Limits
21 - 28 inch	Storm Facilities	BNSF Railroad
30 - 36 inch		Streams
> 42 inch		



2016 SURFACE WATER
COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (ES2)
FIGURE 4-20

KING CREEK BASIN

KC1: Culvert Replacement along King Creek at Soper Hill Road

Replace existing 4-foot span, 3-foot rise box culvert with a 17-foot span, 7-foot rise reinforced concrete box culvert that is 160-feet in length. The culvert shall be countersunk 30 percent and the streambed within the culvert shall be filled with gravel and sediment to comply with WDFW 2013 Guidelines. The average spacing of the steps or cascades should be approximately 26 feet throughout the length of the culvert. Temporary bypass of flow around the work area will be necessary during construction (Figure 4-21).

Estimated Project Cost: \$1,590,000

A list of the capital improvement projects with corresponding project cost estimates and priorities are provided in Table 4-1.


Page Intentionally Left Blank



KC1: Culvert Replacement along King Creek at Soper Hill Rd
 Replace 4'x3' box culvert with a 17'x7' concrete box culvert
 Cost: \$1,590,000
 Priority: Medium



- | | | |
|-------------------|--------------------|------------------------|
| Stormlines | > 42 INCH | Storm Facilities |
| < 8 inch | Catch Basin | Marysville City Limits |
| 8 - 12 inch | CLEANOUT | Urban Growth Boundary |
| 13 - 18 inch | CB Type 1 | Streams |
| 21 - 28 INCH | CB Type 2 | Parcels |
| 30 - 36 INCH | CB Type 3 | |



2016 SURFACE WATER
 COMPREHENSIVE PLAN UPDATE

CIP PROJECTS (KC1)
 FIGURE 4-21

TABLE 4-1
Capital Improvement Projects

Project No.	Previous Project No. (2009)	Project Location	Project Description	Cost	Priority
Quilceda Creek					
QC1	N/A	North of 172 nd at Edward Springs Reservoir	Replace existing 36-inch CMP stormwater pipe with new CPEP pipe	\$381,000	High
QC2	MQ-HH-19	Field north of 152 nd between Smokey Point Boulevard and 51 st Avenue NE	Install Fish Screen in Hayho Creek	\$231,000	Low
QC3	MQ-EC-03/ MQ-EC-05	Field north of 152 nd between 51 st Avenue NE and the BNSF Railroad ⁽¹⁾	Replace existing 30-inch concrete and CMP culverts with 16-foot span, 6-foot rise reinforced concrete box culverts.	\$617,000	Low
QC4A	MQ-HH-16	Hayho Creek between 144 th Avenue NE and 172 nd Street NE ⁽¹⁾	Realign Hayho Creek within existing wetlands	\$1,680,000	Medium
QC4B	MQ-HH-32	North of 152 nd St. NE ⁽¹⁾	Provide 4,400 LF of 48-inch conveyance to serve as a main trunk line for Ponds 1 and 2	\$4,901,000	High
QC4C	MQ-HH-32	Corner of 152 nd St. NE and 43 rd Ave. NE	Construct 3.5-acre Regional Pond 3	\$1,831,000	Medium
QC5A	MQ-EC-13	West side of the BNSF RR between 154 th Drive NE and 172 nd Street NE	Realign Edgecomb Creek and install a 20-acre regional detention pond	\$19,042,000	High
QC5B	MQ-EC-13	Along and east of 51 st Ave. NE ⁽¹⁾	Install 10,550 LF of conveyance pipe ranging from 24-inch to 54-inch.	\$8,517,000	High
QC5C	MQ-EC-13	Between 51 st Ave. NE and BNSF railway	Install 20-acre regional detention pond	\$5,054,000	High
QC6	MQ-EC-01	152 nd Street NE between 51 st Avenue NE and BNSF RR (Edgecomb Creek)	Replace existing 36-inch CMP culvert with new 17-foot span, 6-foot rise reinforced concrete box culvert	\$489,000	Medium
QC7	MQ-MQ-07	152 nd Street NE between BNSF RR and 67 th Avenue NE	Replace existing 30-inch CMP culvert with a 15-foot span, 5-foot rise reinforced concrete box culvert	\$520,000	Medium
QC8	MQ-MQ-04	Strawberry Fields Trail just south of 152 nd Street NE	Replace existing 36-inch CMP culvert with 19-foot span, 7-foot rise reinforced concrete box culvert and restore 1,750 LF of channel bank	\$548,000	Low

TABLE 4-1 -- (continued)
Capital Improvement Projects

Project No.	Previous Project No. (2009)	Project Location	Project Description	Cost	Priority
QC9	MQ-HH-09	43 rd Avenue NE at Emerald Hills Estates	Provide a berm within the existing channel	\$69,000	Low
QC10	MQ-HH-38	Hayho Creek between BNSF RR and 47 th Drive NE ⁽¹⁾	Regrade 850 LF of Hayho Creek and install native riparian vegetation	\$2,882,000	Medium
QC10A	N/A	136 th Street NE at 45 th Avenue NE	Provide 51,000 cf of temporary storage via a pond on the north side of 136 th Street NE and replace 145 LF of 15-inch HDPE with 18-inch CPEP	\$425,000	Medium
QC11	WQ-WQ-08	104 th Street NE between 39 th Drive NE and 42 nd Avenue NE	Replace existing 4-foot span concrete box culvert with a 50-foot prefabricated bridge	\$1,017,000	Medium
QC12	WQ-WQ-09	103 rd Street NE west of 42 nd Avenue NE	Replace 24-inch CMP culvert with 50-foot Bridge	\$980,000	Medium
QC13	MQ-QC-09	State Avenue between 100 th Street NE and 103 rd Place NE	Replace two existing 6-foot span 6-foot rise concrete box culverts with 180-foot prefabricated bridge	\$6,755,000	High
Allen Creek					
AC1	AC-AC-10	95 th Street NE and 67 th Avenue NE	Replace 227 LF of existing 12-inch storm pipe with 18-inch CPEP pipe	\$161,000	Low
AC2	AC-AC-03	88 th Street NE between 60 th Drive NE and 67 th Avenue NE	Replace existing 7-foot span, 5-foot rise concrete box culvert with 25-foot span, 10-foot rise reinforced concrete box culvert and stabilize 50 LF of south bank	\$898,000	High
AC3	AC-JC-12	61 st Street NE	Replace 580 LF of existing 12-inch storm pipe with 420 LF of 15-inch CPEP pipe and 160 LF of new 12-inch CPEP pipe	\$323,000	Low
AC4	AC-JC-11	63 rd Place NE, 63 rd Avenue NE, and 64 th Avenue NE	Replace 1,230 LF of existing 12-inch storm pipe with 450 LF of 18-inch CPEP pipe and 780 LF of 15-inch CPEP pipe	\$654,000	Medium
Ebey Slough North					
ES1	N/A	Historic Downtown Marysville	Green Retrofit Study	\$150,000	High
ES2	ES-DT-03	Treatment Facility at Marina Outfall at Ebey Slough	Water Quality Treatment Facility	\$8,208,000	High

TABLE 4-1 – (continued)
Capital Improvement Projects

Project No.	Previous Project No. (2009)	Project Location	Project Description	Cost	Priority
King Creek					
KC1	N/A	Soper Hill Road at 74 th Drive NE	Replace existing 4-foot span, 3-foot rise concrete box culvert with a 17-foot span, 7-foot rise reinforced concrete box culvert.	\$1,590,000	Medium

(1) Coordination with private property owner(s) will be necessary.

Table 4-2 summarizes the 6-Year Capital Improvement Project Plan. Detailed cost estimates are provided in Appendix B.

These projects are ranked based on the severity of the problem and City input. Other drainage problems may arise in the future and will need to be addressed at that time. In addition, the current Plan will need to be reevaluated and updated as necessary as development and regulatory requirements change.

TABLE 4-2
Capital Improvement Plan (2017 to 2022)

Project No.	Project Name	Project Description	2016 Cost	Year Planned
QC4B	Conveyance for Regional Detention Ponds 1 and 2	Install 4,400 LF of 48-inch conveyance pipe north of 152 nd Street NE	\$4,901,000	2019
QC13	Culvert Removal and Bridge Installation along Quilceda Creek at State Avenue	Install 180-foot prefabricated bridge along State Avenue	\$6,755,000	2018
ES1	Historic Downtown Green Retrofit Study	Green Retrofit Study	\$150,000	2017
ES2	Water Quality Treatment Facility at Downtown Marina Outfall	Water Quality Study	\$8,208,000	2018
QC5A	Edgecomb Creek Channel Realignment	Realign Edgecomb Creek and install a 20-acre regional detention pond	\$19,042,000	2023
QC5B	Edgecomb Creek Conveyance	Install 10,550 LF of conveyance pipe ranging from 24 inch to 54 inch.	\$8,517,000	2022
QC5C	Edgecomb Creek Regional Detention Facility	Install 20-acre regional detention pond	\$5,054,000	2021

CHAPTER 5

FINANCIAL REVIEW

The financial resources available to the City to fund operation and maintenance and capital improvements for stormwater infrastructure, other than general revenue from property taxes, include service charges, general facilities charge (GFCs), grants and loans. This chapter provides a summary of potential funding sources if additional funds are needed. The City has formed a stormwater utility to fund ongoing operation and maintenance, and capital improvements. An analysis to fund the planned stormwater program is provided.

According to information provided by the City's financial staff, the City's 2015 stormwater related operating expenditures were \$1,837,000. Chapter 4 shows a range from approximately \$150,000 to \$19 million per year in the 6-year plan for capital project expenditures. The City's stormwater-related revenues are found to be adequate to support the planned operational expenses. However, there are significant funding deficiencies for funding capital improvements over the next 20 years.

STORMWATER UTILITY

RCW Chapter 35.67 allows the City to form a stormwater management utility to provide for the planning, development, management, operation, maintenance, use, and improvement of the storm drainage system. A utility is an enterprise that is operated or regulated by a government entity. The enterprise funds are predominantly self-sustaining and account for the acquisition, operation, and maintenance of governmental facilities.

The City of Marysville stormwater utility formation and rate structure is codified in Marysville Municipal Code Chapter 14.19. The current 2016 stormwater service charge is set at \$11.26 per month per equivalent residential unit (ERU) or single-family residence (SFR). One ERU corresponds to 3,200 square feet of impervious surface area for non-single-family properties per MMC Chapter 14.19.050. Therefore, for non-single-family residential parcels, the stormwater service charge would be \$11.26 for every 3,200 square feet of impervious surface area per parcel. Also, per MMC Chapter 14.17.010, the City charges a one-time Connection Charge of \$95 per new ERU.

The monthly service charge is a fee levied by the City upon all developed property within the City's boundary. The stormwater service charge pays for improvements and maintenance to address drainage and flooding problems within the City. It was adopted to protect the environment and comply with new regulations protecting drainage systems.

Knowing the total number of ERUs in the City is useful in determining the monthly service charge required to support the O&M program and planned capital improvements. Using 2015 rate revenues of \$4,166,817 and a monthly 2015 service rate of \$11.04, it is estimated that the City collected revenue from 31,448 ERUs (= \$4.1 million / \$11.04 per ERU / 12 months).

CAPITAL IMPROVEMENT PLAN

The recommended capital improvements for the stormwater utility are detailed in Chapter 4. The list of projects, recommended schedule for implementation of the 6-year CIP, and their costs are shown in Table 5-1.

TABLE 5-1

Planned Capital Improvements 2017-2023⁽¹⁾

Capital Expense	2017	2018	2019	2020	2021	2022	2023
QC13: Culvert Removal and Bridge Installation along Quilceda Creek at State Avenue		\$6,755,000					
ES2: Water Quality Treatment Facility at Downtown Marina Outfall		\$8,208,000					
QC4B: Conveyance for Regional Detention Ponds 1 and 2			\$4,901,000				
ES1: Historic Downtown Green Retrofit Study	\$150,000						
QC5A: Edgecomb Creek Channel Realignment							\$19,042,000
QC5B: Edgecomb Creek Conveyance						\$8,517,000	
QC5C: Edgecomb Creek Regional Detention Facility					\$5,054,000		

(1) Project costs reflect estimated Year 2016 costs. A cost escalation of approximately 3 percent should be used when budgeting for the project.

OPERATIONS AND MAINTENANCE AND EQUIPMENT PURCHASE

The annual stormwater operating expenses is shown below. In 2015, the annual stormwater maintenance cost based on City records is \$1,836,340. Table 5-2 shows 2015 operating and maintenance expenses.

TABLE 5-2

2015 Operating and Maintenance Expenses

Expenditures	2015
Regular Salary	\$566,860
Seasonal Salary	\$30,965
Overtime	\$124
Social Security	\$44,916
Retirement	\$55,738
Health Insurance	\$110,748
Workmen's Comp.	\$15,952
Unemployment Comp.	\$1,172
Uniforms/Clothing	\$858
Office and Operating	\$49,094
Fuel Consumed	\$1,121
Small Tools	\$4,708
Flail Mower	\$17,987
Pipe Ranger	\$24,580
Professional Services	\$229,503
Surface Water	\$18,028
Communication	\$6,923
Travel	\$0
Operating Rentals	\$1,152
Public Utility Service	\$5,918
Repairs and Maintenance	\$54,728
Miscellaneous	\$28,521
NPDES Permit	\$49,688
Qwuloolt Mitigation	\$33,274
Qwuloolt Out.	\$3,891
State Taxes	\$69,233
Operating Permits	\$20,794
City Taxes	\$326,432
Machinery and Equipment	\$17,175
Facilities Maintenance	\$507
Small Engine Shop	\$15,443
Computer Services	\$30,291
Total	\$1,836,324

SERVICE CHARGE DETERMINATION

The 6-year analysis assumes the capital improvement projects from Table 5-1 are funded from monthly service rates and capital facility charges. As an alternative, low interest loans from the P WTF program may be used when necessary. Use of low interest loans may be financially favorable to self-financing as long as the interest costs of the loans are less than the interest that can be earned from reserve funds.

The budget forecast assumptions are included in Table 5-3. The stormwater utility expenses are taken from the 2015 budget. An increase of 0.5 percent is assumed for ERUs, and a 2.0 percent increase in project and O&M costs is assumed as a conservative measure in assessing the budget.

TABLE 5-3

Budget Forecast Assumptions and Baseline Operating Costs

Item	Assumption
Number of ERUs in December 2015	
Total ERUs for Rate Analysis	31,448
Escalation Factors	
Growth ⁽¹⁾	2.0%
Inflation (Yearly O&M Expenses)	2.0%
Construction Cost Inflation	3.0%
Investment Interest	1.0%
Revenue Bond	4.6%
Taxes	
State Excise Tax	1.8%

(1) Source: City of Marysville 2015 Comprehensive Plan.

PRELIMINARY RATE ANALYSIS

Table 5-4 presents a simple, cash-based rate analysis based on the recommended project financing. The preliminary rate analysis is based on the following assumptions.

1. The rate of growth (ERUs), O&M costs, and project costs assumed at a 2.0 percent annual increase for each.
2. The utility has a zero balance at the start of 2016. This does not reflect actual conditions but since the City does not track the cash balance of each of its utilities, the beginning balance specifically for stormwater purposes could not be determined.

Based on the assumptions listed above, the financial forecast shows the amount of incoming revenues covering the anticipated operating expenses. Using the assumed

project completion dates in Table 5-1, the stormwater service charge does not have sufficient funds to accommodate the proposed 6-year CIP. Without an increase in service charges, these projects would need to be funded via other means such as grants or loans as explained in the next Section. At a minimum, it is recommended that the stormwater service charge be increased annually per a cost-of living or consumer price index factor.

**TABLE 5-4
Financial Analysis**

Year	2017	2018	2019	2020	2021	2022	2023
Beginning Fund Balance ⁽¹⁾	-	\$2,332,729	(\$1,801,470)	(\$3,937,264)	(\$1,021,047)	(\$3,000,934)	(\$8,278,743)
ERUs	31,448	32,077	32,718	33,373	34,040	34,721	35,415
Monthly Storm Service Rate	\$11.49	\$11.71	\$11.95	\$12.19	\$12.43	\$12.68	\$12.93
Rate Revenue	\$4,334,193	\$4,509,294	\$4,691,470	\$4,881,005	\$5,078,198	\$5,283,357	\$5,496,805
Connection Fees	\$59,751	\$60,946	\$62,164	\$63,408	\$64,676	\$65,969	\$67,289
Total Revenue	\$4,393,944	\$4,570,240	\$4,753,634	\$4,944,413	\$5,142,874	\$5,349,327	\$5,564,094
Yearly O&M Costs	\$1,911,215	\$1,949,439	\$1,988,428	\$2,028,196	\$2,068,760	\$2,110,136	\$2,152,338
Operating Surplus (Deficiency)	\$2,482,729	\$2,620,801	\$2,765,207	\$2,916,217	\$3,074,113	\$3,239,191	\$3,411,755
CIP Projects							
QC13: Culvert Removal and Bridge Installation Along Quilceda Creek at State Avenue		\$6,755,000					
ES2: Water Quality Treatment Facility at Downtown Marina Outfall		\$8,208,000					
QC4B: Conveyance for Regional Detention Ponds 1 and 2			\$4,901,000				
ES1: Historic Downtown Green Retrofit Study	\$150,000						
QC5A: Edgcomb Creek Channel Realignment							\$19,042,000
QC5B: Edgcomb Creek Conveyance						\$8,517,000	
QC5C: Edgcomb Creek Regional Detention Facility					\$5,054,000		
CIP Total	\$150,000	\$14,963,000	\$4,901,000	-	\$5,054,000	\$8,517,000	\$19,042,000
Yearly Surplus (Deficiency)	\$2,332,729	(\$10,009,470)	(\$12,145,264)	(\$9,229,047)	(\$11,208,934)	(\$16,486,743)	(\$32,116,987)

(1) The actual beginning fund balance for 2016 could not be determined from City financial records. The ending balance in December 2016 is used to predict the beginning fund balance for 2017.

GRANT AND LOAN PROGRAMS

Grants and loans can be used to fund capital improvement projects, but cannot be used to fund operation and maintenance. Within the State of Washington, there are several grant and loan funds available for capital improvements. Among these are the Public Works Trust Fund (P WTF), Centennial Clean Water Fund (CCWF), and the State Revolving Fund (SRF). The various grant and loan programs are briefly described below for reference.

Public Works Trust Fund

This program is a revolving fund loan designed to help local governments finance needed public works projects through low-interest loans and technical assistance. It was established by the Washington State Legislature in 1985 and is administered by the Public Works Board. The Legislature cancelled the 2010 to 2016 biennium funding cycles. Loan repayments and tax revenue streams that fund the program continued to be deposited in the fund and yet, it has remained uncertain as to what level of funding may be available through the program in the future. Currently, the Board is tentatively offering \$100 million state-wide in construction loans for the 2017 funding cycle.

Department of Ecology Integrated Funding Program

The Department of Ecology administers several loan and grant programs that can be used to fund the following:

- Stormwater capital improvements including stormwater system retrofits;
- Low-impact development projects;
- Inventories of stormwater sources;
- Public education and communication;
- Review and preparation of stormwater regulations;
- Mapping;
- Source control activities; and
- Establishing and refining stormwater utilities.

The funding programs include the Centennial Clean Water Grant program (state funds), the Clean Water Act Section 319 Grant program (federal funds), the Stormwater Financial Assistance Grant Program (state funds) and the Washington State Revolving Fund Loan program (federal and state funds). A common application is available for funding from the Ecology-administered programs. The programs are competitive and the majority of the funding available is in the form of low-interest loans.

DEBT FINANCING

Two forms of debt financing are available for capital improvements including general obligation (G.O.) bonds and revenue bonds. G.O. bonds are backed by the "full faith and

credit of the City” and are paid for through levies. These bonds require voter approval before they can be implemented. A less common means of financing capital improvements associated with stormwater projects is through the use of revenue bonds. The City, like other municipalities, is capable of issuing tax-exempt bonds. The principal and interest of such bonds are repaid from revenue generated from a utility, such as a water, sewer, or stormwater utility. This type of funding may be offered without voter approval. However, in order to qualify to sell revenue bonds, the City must establish that its net operating income is equal to or greater than its debt coverage factor, typically 1.4, multiplied by the annual principal and interest due for all outstanding bonded indebtedness. Utility rates have to be set high enough to ensure revenue bond repayment.


FUTURE CAPITAL IMPROVEMENT PLAN

The total cost, in 2016 dollars, of the 2017-2023 CIP is over \$52 million. The stormwater utility revenues alone are adequate to support the planned operational expenses. However, they are inadequate to cover the capital expenses over the 6-year planning period, without any service rate increases. Further, the amount of funds available for capital projects will decrease due to increasing O&M costs. However, the total cost of the projects scheduled for years 7 through 20 is over \$15 million (2016 dollars), for which there would be a significant revenue shortfall, were rates to remain unchanged.

Page Intentionally Left Blank.

APPENDIX A
STORMWATER BASE MAP

Page Intentionally Left Blank



APPENDIX B
COST ESTIMATES

Page Intentionally Left Blank

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC1: Stormwater Pipe Replacement at Edward Springs Reservoir
 September 1, 2016
 G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1	LS \$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS \$ 20,000	\$ 20,000
3.	Project Temporary Traffic Control	1	LS \$ 10,000	\$ 10,000
4.	Locate Existing Utilities	1	LS \$ 2,000	\$ 2,000
5.	Survey	1	LS \$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1	LS \$ 3,000	\$ 3,000
7.	Dewatering	1	LS \$ 10,000	\$ 10,000
8.	Trench Excavation Safety Systems	400	LF \$ 5	\$ 2,000
9.	Excavation Incl. Haul	540	CY \$ 40	\$ 21,600
10.	Remove Existing Pipe	400	LF \$ 30	\$ 12,000
11.	Crushed Surfacing Base Course	720	TN \$ 35	\$ 25,200
12.	36-inch Storm Pipe incl. Bedding	400	LF \$ 250	\$ 100,000
13.	Connect to Drainage Structure	2	EA \$ 700	\$ 1,400
14.	Surface Restoration (seeding, fertilizing, planting, etc)	230	SY \$ 7	\$ 1,610
15.	Project Documentation	1	LS \$ 2,000	\$ 2,000
	Subtotal			\$ 217,000
	Construction Contingencies (20%)			\$ 44,000
	Sales Tax (9.1%)			\$ 20,000
	Total Construction Cost			\$ 281,000
	Design, Engineering & Construction Management (25%)			\$ 71,000
	Permitting (10%)			\$ 29,000
	Easements (Temporary & Permanent)	0	AC \$ 40,000	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	0	EA \$ 1,000	\$ -
TOTAL PROJECT COST				\$ 381,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC2: Fish Screen Installation along Hayho Creek at 160th Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 11,000	\$ 11,000
3.	Project Temporary Traffic Control	1	LS	\$ 2,000	\$ 2,000
4.	Locate Existing Utilities	1	LS	\$ 1,000	\$ 1,000
5.	Survey	1	LS	\$ 1,000	\$ 1,000
6.	Temporary Erosion Control	1	LS	\$ 7,500	\$ 7,500
7.	Dewatering	1	LS	\$ 7,500	\$ 7,500
8.	Clearing and Grubbing	0.25	AC	\$ 15,000	\$ 3,750
9.	Temporary Stream Bypass	1	LS	\$ 25,000	\$ 25,000
10.	Structure Excavation	5	CY	\$ 40	\$ 200
11.	Fish Screen Barrier	1	EA	\$ 35,000	\$ 35,000
12.	Vertical In-Stream Trash Rack	1	EA	\$ 15,000	\$ 15,000
13.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 112,000
	Construction Contingencies (20%)				\$ 23,000
	Sales Tax (9.1%)				\$ 11,000
	Total Construction Cost				\$ 146,000
	Design, Engineering & Construction Management (25%)				\$ 37,000
	Permitting (25%)				\$ 37,000
	Easements (Temporary & Permanent)	5856	SF	\$ 1	\$ 6,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	5	EA	\$ 1,000	\$ 5,000
TOTAL PROJECT COST					\$ 231,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC3: Field Access Culvert Replacement along Edgecomb Creek
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
Schedule A Culvert 1					
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 15,000	\$ 15,000
3.	Project Temporary Traffic Control	1	LS	\$ 3,000	\$ 3,000
4.	Locate Existing Utilities	1	LS	\$ 2,000	\$ 2,000
5.	Survey	1	LS	\$ 3,000	\$ 3,000
6.	Temporary Erosion Control	1	LS	\$ 5,000	\$ 5,000
7.	Dewatering	1	LS	\$ 10,000	\$ 10,000
8.	Temporary Bypass	1	LS	\$ 25,000	\$ 25,000
9.	Excavation Incl. Haul	210	CY	\$ 40	\$ 8,400
10.	Remove Existing Pipe	30	LF	\$ 30	\$ 900
11.	Crushed Surfacing Base Course	20	TN	\$ 35	\$ 700
12.	Streambed Gravel	110	TN	\$ 50	\$ 5,500
13.	Gravel Borrow	50	TN	\$ 26	\$ 1,300
14.	16-ft Span Reinforced Concrete Box Culvert	30	LF	\$ 2,700	\$ 81,000
15.	Surface Restoration (seeding, fertilizing, planting, etc)	90	SY	\$ 7	\$ 630
16.	Project Documentation	1	LS	\$ 1,000	\$ 1,000
Schedule A Subtotal					\$ 164,000
Schedule B Culvert 2					
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 15,000	\$ 15,000
3.	Project Temporary Traffic Control	1	LS	\$ 3,000	\$ 3,000
4.	Locate Existing Utilities	1	LS	\$ 2,000	\$ 2,000
5.	Survey	1	LS	\$ 3,000	\$ 3,000
6.	Temporary Erosion Control	1	LS	\$ 5,000	\$ 5,000
7.	Dewatering	1	LS	\$ 10,000	\$ 10,000
8.	Temporary Bypass	1	LS	\$ 25,000	\$ 25,000
9.	Excavation Incl. Haul	120	CY	\$ 40	\$ 4,800
10.	Remove Existing Pipe	27	LF	\$ 30	\$ 810
11.	Crushed Surfacing Base Course	20	TN	\$ 35	\$ 700
12.	Streambed Gravel	130	TN	\$ 50	\$ 6,500
13.	Gravel Borrow	40	TN	\$ 26	\$ 1,040
14.	16-ft Span Reinforced Concrete Box Culvert	24	LF	\$ 3,250	\$ 78,000
15.	Surface Restoration (seeding, fertilizing, planting, etc)	90	SY	\$ 7	\$ 630
16.	Project Documentation	1	LS	\$ 1,000	\$ 1,000
Schedule B Subtotal					\$ 158,000
Project Subtotal					\$ 322,000
Construction Contingencies (20%)					\$ 65,000
Sales Tax (9.1%)					\$ 30,000

Total Construction Cost		\$ 417,000
Design, Engineering & Construction Management (25%)		\$ 105,000
Permitting (20%)		\$ 84,000
Easements (Temporary & Permanent)	10000 SF	\$ 10,000
Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	1 EA	\$ 1,000
TOTAL PROJECT COST		\$ 617,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC4A: Hayho Creek Channel Realignment (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 62,000	\$ 62,000
3.	Project Temporary Traffic Control	1 LS	\$ 7,000	\$ 7,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1 LS	\$ 5,000	\$ 5,000
7.	Dewatering	1 LS	\$ 150,000	\$ 150,000
8.	Clearing and Grubbing	4.5 AC	\$ 15,000	\$ 67,500
9.	Excavation Incl. Haul	9,500 CY	\$ 5	\$ 47,500
10.	Enhanced Surface Restoration (wetland plantings, seeding, etc)	21,780 SY	\$ 15	\$ 326,700
11.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 676,000
	Construction Contingencies (20%)			\$ 136,000
	Sales Tax (9.1%)			\$ 62,000
	Total Construction Cost			\$ 874,000
	Design, Engineering & Construction Management(25%)			\$ 219,000
	Permitting (20%)			\$ 175,000
	Easements (Temporary & Permanent)	10 AC	\$ 40,000	\$ 400,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	12 EA	\$ 1,000	\$ 12,000
TOTAL PROJECT COST				\$ 1,680,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC4B: Conveyance for Regional Detention Pond No. 2 (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 238,000	\$ 238,000
3.	Project Temporary Traffic Control	1 LS	\$ 21,000	\$ 21,000
4.	Locate Existing Utilities	1 LS	\$ 5,000	\$ 5,000
5.	Survey	1 LS	\$ 20,000	\$ 20,000
6.	Temporary Erosion Control	1 LS	\$ 2,000	\$ 2,000
7.	Dewatering	1 LS	\$ 240,000	\$ 240,000
8.	Clearing and Grubbing	4.5 AC	\$ 15,000	\$ 68,182
9.	Trench Excavation Safety Systems	4400 LF	\$ 5	\$ 22,000
10.	Excavation Incl. Haul	6000 CY	\$ 40	\$ 240,000
11.	Gravel Borrow	50 TN	\$ 26	\$ 1,300
12.	42-inch Storm Pipe incl. Bedding	4400 LF	\$ 300	\$ 1,320,000
13.	72-inch Type II Storm Manhole	15 EA	\$ 7,000	\$ 102,667
14.	Enhanced Surface Restoration (wetland plantings, seeding, etc)	22000 SY	\$ 15	\$ 330,000
15.	Project Documentation	1 LS	\$ 5,000	\$ 5,000
	Subtotal			\$ 2,617,000
	Construction Contingencies (20%)			\$ 524,000
	Sales Tax (9.1%)			\$ 239,000
	Total Construction Cost			\$ 3,380,000
	Design, Engineering & Construction Management(25%)			\$ 845,000
	Permitting (20%)			\$ 676,000
TOTAL PROJECT COST				\$ 4,901,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC4C: Hayho Creek Regional Detention Pond No. 3 (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 89,000	\$ 89,000
3.	Project Temporary Traffic Control	1 LS	\$ 9,000	\$ 9,000
4.	Locate Existing Utilities	1 LS	\$ 1,000	\$ 1,000
5.	Survey	1 LS	\$ 2,000	\$ 2,000
6.	Temporary Erosion Control	1 LS	\$ 4,050	\$ 4,050
7.	Dewatering	1 LS	\$ 113,400	\$ 113,400
8.	Clearing and Grubbing	4 AC	\$ 15,000	\$ 52,500
9.	Excavation Incl. Haul	40,000 CY	\$ 5	\$ 200,000
10.	Inlet and Outlet Controls	1 LS	\$ 240,000	\$ 240,000
11.	Enhanced Surface Restoration (wetland plantings, seeding, etc)	16,940 SY	\$ 15	\$ 254,100
12.	Project Documentation	1 LS	\$ 10,000	\$ 10,000
	Subtotal			\$ 977,000
	Construction Contingencies (20%)			\$ 196,000
	Sales Tax (9.1%)			\$ 89,000
	Total Construction Cost			\$ 1,262,000
	Design, Engineering & Construction Management(25%)			\$ 316,000
	Permitting (20%)			\$ 253,000
TOTAL PROJECT COST				\$ 1,831,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC5A: Edgcomb Creek Channel Realignment (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 754,000	\$ 754,000
3.	Project Temporary Traffic Control	1 LS	\$ 75,000	\$ 75,000
4.	Locate Existing Utilities	1 LS	\$ 10,000	\$ 10,000
5.	Survey	1 LS	\$ 15,000	\$ 15,000
6.	Temporary Erosion Control	1 LS	\$ 80,000	\$ 80,000
7.	Clearing and Grubbing	68 AC	\$ 15,000	\$ 1,020,000
8.	Excavation Incl. Haul	415,700 CY	\$ 5	\$ 2,078,500
9.	Fish Passable Culvert	10 EA	\$ 100,000	\$ 1,000,000
10.	Large Woody Debris	56 EA	\$ 2,700	\$ 151,200
11.	Riparian Plantings	309,800 SY	\$ 10	\$ 3,098,000
12.	Project Documentation	1 LS	\$ 5,000	\$ 5,000
	Subtotal			\$ 8,288,000
	Construction Contingencies (20%)			\$ 1,658,000
	Sales Tax (9.1%)			\$ 755,000
	Total Construction Cost			\$ 10,701,000
	Design, Engineering & Construction Management(25%)			\$ 2,676,000
	Permitting (20%)			\$ 2,141,000
	Easements (Temporary & Permanent)	87.5 AC	\$ 40,000	\$ 3,500,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	24 EA	\$ 1,000	\$ 24,000
TOTAL PROJECT COST				\$ 19,042,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC5B: Edgecomb Creek Conveyance (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 414,000	\$ 414,000
3.	Project Temporary Traffic Control	1 LS	\$ 41,000	\$ 41,000
4.	Locate Existing Utilities	1 LS	\$ 5,000	\$ 5,000
5.	Survey	1 LS	\$ 20,000	\$ 20,000
6.	Temporary Erosion Control	1 LS	\$ 25,000	\$ 25,000
7.	Dewatering	1 LS	\$ 350,000	\$ 350,000
8.	Clearing and Grubbing	1.0 AC	\$ 15,000	\$ 15,000
9.	Trench Excavation Safety Systems	7,950 LF	\$ 5	\$ 39,750
10.	Excavation Incl. Haul	18,000 CY	\$ 40	\$ 720,000
11.	Gravel Borrow	130 TN	\$ 26	\$ 3,380
12.	24-inch Storm Pipe incl. Bedding	2,100 LF	\$ 120	\$ 252,000
13.	30-inch Storm Pipe incl. Bedding	1,300 LF	\$ 180	\$ 234,000
14.	36-inch Storm Pipe incl. Bedding	3,250 LF	\$ 250	\$ 812,500
15.	42-inch Storm Pipe incl. Bedding	1,300 LF	\$ 300	\$ 390,000
16.	54-inch Storm Pipe incl. Bedding	2,600 LF	\$ 350	\$ 910,000
17.	48-inch Type II Storm Manhole	7 EA	\$ 4,000	\$ 28,000
18.	54-inch Type II Storm Manhole	4 EA	\$ 4,500	\$ 18,000
19.	60-inch Type II Storm Manhole	10 EA	\$ 5,000	\$ 50,000
20.	72-inch Type II Storm Manhole	4 EA	\$ 7,000	\$ 28,000
21.	84-inch Type II Storm Manhole	8 EA	\$ 10,000	\$ 80,000
22.	Surface Restoration (seeding, fertilizing, planting, etc)	14,600 SY	\$ 7	\$ 102,200
23.	Project Documentation	1 LS	\$ 10,000	\$ 10,000
	Subtotal			\$ 4,549,000
	Construction Contingencies (20%)			\$ 910,000
	Sales Tax (9.1%)			\$ 414,000
	Total Construction Cost			\$ 5,873,000
	Design, Engineering & Construction Management(25%)			\$ 1,469,000
	Permitting (20%)			\$ 1,175,000
	TOTAL PROJECT COST			\$ 8,517,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

QC5C: Edgecomb Creek Regional Detention Facility (North Marysville Master Drainage Plan)

September 27, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 246,000	\$ 246,000
3.	Project Temporary Traffic Control	1 LS	\$ 25,000	\$ 25,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1 LS	\$ 20,000	\$ 20,000
7.	Dewatering	1 LS	\$ 500,000	\$ 500,000
8.	Clearing and Grubbing	15 AC	\$ 15,000	\$ 231,000
9.	Excavation Incl. Haul	174,000 CY	\$ 5	\$ 870,000
10.	Inlet and Outlet Controls	2 LS	\$ 120,000	\$ 240,000
11.	Chainlink Fence	760 LF	\$ 35	\$ 26,600
12.	Surface Restoration (seeding, fertilizing, planting, etc)	74,600 SY	\$ 7	\$ 522,200
13.	Project Documentation	1 LS	\$ 10,000	\$ 10,000
	Subtotal			\$ 2,699,000
	Construction Contingencies (20%)			\$ 540,000
	Sales Tax (9.1%)			\$ 246,000
	Total Construction Cost			\$ 3,485,000
	Design, Engineering & Construction Management(25%)			\$ 872,000
	Permitting (20%)			\$ 697,000
TOTAL PROJECT COST				\$ 5,054,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC6: Culvert Replacement along Edgcomb Creek at 152nd Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 24,000	\$ 24,000
3.	Project Temporary Traffic Control	1	LS	\$ 7,000	\$ 7,000
4.	Locate Existing Utilities	1	LS	\$ 3,000	\$ 3,000
5.	Survey	1	LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1	LS	\$ 10,000	\$ 10,000
7.	Dewatering	1	LS	\$ 15,000	\$ 15,000
8.	Temporary Bypass	1	LS	\$ 35,000	\$ 35,000
9.	Excavation Incl. Haul	350	CY	\$ 40	\$ 14,000
10.	Remove Existing Pipe	42	LF	\$ 30	\$ 1,260
11.	Sawcutting	50	LF	\$ 3	\$ 150
12.	Remove Asphalt Pavement	60	SY	\$ 5	\$ 300
13.	Crushed Surfacing Base Course	20	TN	\$ 35	\$ 700
14.	Gravel Borrow	70	TN	\$ 26	\$ 1,820
15.	Streambed Gravel	150	TN	\$ 50	\$ 7,500
16.	HMA, CL 1/2-in PG 64-22	11	TN	\$ 145	\$ 1,600
17.	17-ft Span Reinforced Concrete Box Culvert	42	LF	\$ 3,000	\$ 126,000
18.	Surface Restoration (seeding, fertilizing, planting, etc)	50	SY	\$ 7	\$ 350
19.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 256,000
	Construction Contingencies (20%)				\$ 52,000
	Sales Tax (9.1%)				\$ 24,000
	Total Construction Cost				\$ 332,000
	Design, Engineering & Construction Management (25%)				\$ 83,000
	Permitting (20%)				\$ 67,000
	Easements (Temporary & Permanent)	5000	SF	\$ 1	\$ 5,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	2	EA	\$ 1,000	\$ 2,000
TOTAL PROJECT COST					\$ 489,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC7: Culvert Replacement along Olaf Strad Creek at 152nd Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 25,000	\$ 25,000
3.	Project Temporary Traffic Control	1 LS	\$ 8,000	\$ 8,000
4.	Locate Existing Utilities	1 LS	\$ 3,000	\$ 3,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1 LS	\$ 10,000	\$ 10,000
7.	Dewatering	1 LS	\$ 15,000	\$ 15,000
8.	Temporary Bypass	1 LS	\$ 35,000	\$ 35,000
9.	Excavation Incl. Haul	400 CY	\$ 40	\$ 16,000
10.	Remove Existing Pipe	53 LF	\$ 30	\$ 1,590
11.	Sawcutting	50 LF	\$ 3	\$ 150
12.	Remove Asphalt Pavement	60 SY	\$ 5	\$ 300
13.	Crushed Surfacing Base Course	20 TN	\$ 35	\$ 700
14.	Gravel Borrow	80 TN	\$ 26	\$ 2,080
15.	Streambed Gravel	150 TN	\$ 50	\$ 7,500
16.	HMA, CL 1/2-in PG 64-22	11 TN	\$ 145	\$ 1,600
17.	15-ft Span Reinforced Concrete Box Culvert	53 LF	\$ 2,600	\$ 137,800
18.	Surface Restoration (seeding, fertilizing, planting, etc)	50 SY	\$ 7	\$ 350
19.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 273,000
	Construction Contingencies (20%)			\$ 55,000
	Sales Tax (9.1%)			\$ 25,000
	Total Construction Cost			\$ 353,000
	Design, Engineering & Construction Management (25%)			\$ 89,000
	Permitting (20%)			\$ 71,000
	Easements (Temporary & Permanent)	5000 SF	\$ 1	\$ 5,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	2 EA	\$ 1,000	\$ 2,000
TOTAL PROJECT COST				\$ 520,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

**QC8: Culvert Replacement and Channel Restoration along Middle Fork Quilceda Creek at
Strawberry Fields Trail**

September 1, 2016
G & O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 27,000	\$ 27,000
3.	Project Temporary Traffic Control	1 LS	\$ 13,000	\$ 13,000
4.	Locate Existing Utilities	1 LS	\$ 3,000	\$ 3,000
5.	Survey	1 LS	\$ 3,000	\$ 3,000
6.	Temporary Erosion Control	1 LS	\$ 15,000	\$ 15,000
7.	Dewatering	1 LS	\$ 16,000	\$ 16,000
8.	Clearing and Grubbing	0.25 AC	\$ 15,000	\$ 3,750
9.	Temporary Bypass	1 LS	\$ 15,000	\$ 15,000
10.	Structure Excavation	200 CY	\$ 40	\$ 8,000
11.	Remove Existing Pipe	21 LF	\$ 30	\$ 630
12.	Crushed Surfacing Base Course	10 TN	\$ 35	\$ 350
13.	Gravel Borrow	40 TN	\$ 26	\$ 1,040
14.	Streambed Gravel	110 TN	\$ 50	\$ 5,500
15.	HMA, CL 1/2-in PG 64-22	10 TN	\$ 145	\$ 1,450
16.	19-ft Span Reinforced Concrete Box Culvert	21 LF	\$ 3,900	\$ 81,900
17.	Large Woody Debris	25 EA	\$ 2,700	\$ 67,500
18.	Riparian Plantings	2420 SY	\$ 10	\$ 24,200
19.	Surface Restoration (seeding, fertilizing, planting, etc)	340 SY	\$ 7	\$ 2,380
20.	Project Documentation	1 LS	\$ 1,000	\$ 1,000
	Subtotal			\$ 291,000
	Construction Contingencies (20%)			\$ 59,000
	Sales Tax (9.1%)			\$ 27,000
	Total Construction Cost			\$ 377,000
	Design, Engineering & Construction Management (25%)			\$ 95,000
	Permitting (20%)			\$ 76,000
	Easements (Temporary & Permanent)	SF	\$ 1	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	EA	\$ 1,000	\$ -
TOTAL PROJECT COST				\$ 548,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC9: Berm Installation at 43rd Avenue and Emerald Hills Estates
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 3,000	\$ 3,000
3.	Project Temporary Traffic Control	1	LS	\$ 1,000	\$ 1,000
4.	Locate Existing Utilities	1	LS	\$ 1,000	\$ 1,000
5.	Survey	1	LS	\$ 1,000	\$ 1,000
6.	Temporary Erosion Control	1	LS	\$ 1,000	\$ 1,000
7.	Dewatering	1	LS	\$ 5,000	\$ 5,000
8.	Clearing and Grubbing	0.25	AC	\$ 15,000	\$ 3,750
9.	Excavation Incl. Haul	20	CY	\$ 40	\$ 800
10.	Embankment Compaction	40	CY	\$ 30	\$ 1,200
11.	Quarry Spalls	10	TN	\$ 60	\$ 600
12.	Riparian Plantings	1210	SY	\$ 10	\$ 12,100
13.	Project Documentation	1	LS	\$ 1,000	\$ 1,000
	Subtotal				\$ 33,000
	Construction Contingencies (20%)				\$ 7,000
	Sales Tax (9.1%)				\$ 4,000
	Total Construction Cost				\$ 44,000
	Design, Engineering & Construction Management (25%)				\$ 11,000
	Permitting (20%)				\$ 9,000
	Easements (Temporary & Permanent)	4000	SF	\$ 1	\$ 4,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	1	EA	\$ 1,000	\$ 1,000
TOTAL PROJECT COST					\$ 69,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC10: Stabilization of Hayho Creek between the BNSF Railroad and 47th Drive NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 134,000	\$ 134,000
3.	Project Temporary Traffic Control	1 LS	\$ 27,000	\$ 27,000
4.	Locate Existing Utilities	1 LS	\$ 1,000	\$ 1,000
5.	Survey	1 LS	\$ 1,000	\$ 1,000
6.	Temporary Erosion Control	1 LS	\$ 95,000	\$ 95,000
7.	Dewatering	1 LS	\$ 95,000	\$ 95,000
8.	Clearing and Grubbing	0.40 AC	\$ 15,000	\$ 6,000
9.	Fish Removal	1 LS	\$ 25,000	\$ 25,000
10.	Excavation Incl. Haul	650 CY	\$ 40	\$ 26,000
11.	Streambed Gravel	290 TN	\$ 50	\$ 14,500
12.	Stream Boulders	180 EA	\$ 400	\$ 72,000
13.	Chainlink Fence	1740 LF	\$ 35	\$ 60,900
14.	Cribwalls	870 SF	\$ 400	\$ 348,000
15.	Vegetated Geogrid	870 SF	\$ 15	\$ 13,050
16.	Coir Log	1300 LF	\$ 18	\$ 23,400
17.	Willow Fascines	500 LF	\$ 25	\$ 12,500
18.	Large Woody Debris	180 EA	\$ 2,700	\$ 486,000
19.	Riparian Plantings	1000 SY	\$ 10	\$ 10,000
20.	Surface Restoration (seeding, fertilizing, planting, etc)	2000 SY	\$ 7	\$ 14,000
21.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 1,468,000
	Construction Contingencies (20%)			\$ 294,000
	Sales Tax (9.1%)			\$ 134,000
	Total Construction Cost			\$ 1,896,000
	Design, Engineering & Construction Management (25%)			\$ 474,000
	Permitting (25%)			\$ 474,000
	Easements (Temporary & Permanent)	21780 SF	\$ 1	\$ 22,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	16 EA	\$ 1,000	\$ 16,000
TOTAL PROJECT COST				\$ 2,882,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC10-A: Runoff Storage along 136th Street NE at 45th Avenue
 September 1, 2016
 G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 21,000	\$ 21,000
3.	Project Temporary Traffic Control	1	LS	\$ 10,000	\$ 10,000
4.	Locate Existing Utilities	1	LS	\$ 2,000	\$ 2,000
5.	Survey	1	LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1	LS	\$ 3,000	\$ 3,000
7.	Dewatering	1	LS	\$ 25,000	\$ 25,000
8.	Excavation Incl. Haul	3700	CY	\$ 40	\$ 148,000
9.	18-inch Storm Pipe incl. Bedding	150	LF	\$ 60	\$ 9,000
10.	Surface Restoration (seeding, fertilizing, planting, etc)	500	SY	\$ 7	\$ 3,500
11.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 230,000
	Construction Contingencies (20%)				\$ 46,000
	Sales Tax (9.1%)				\$ 21,000
	Total Construction Cost				\$ 297,000
	Design, Engineering & Construction Management (25%)				\$ 75,000
	Permitting (10%)				\$ 30,000
	Easements (Temporary & Permanent)	0.54	AC	\$ 40,000	\$ 22,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	1	EA	\$ 1,000	\$ 1,000
TOTAL PROJECT COST					\$ 425,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC11: Culvert Removal and Bridge Installation at 104th Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 48,000	\$ 48,000
3.	Project Temporary Traffic Control	1 LS	\$ 10,000	\$ 10,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Utility Relocation	1 LS	\$ 10,000	\$ 10,000
7.	Temporary Erosion Control	1 LS	\$ 20,000	\$ 20,000
8.	Dewatering	1 LS	\$ 15,000	\$ 15,000
9.	Clearing and Grubbing	0.10 AC	\$ 15,000	\$ 1,500
10.	Temporary Bypass	1 LS	\$ 15,000	\$ 15,000
11.	Excavation Incl. Haul	800 CY	\$ 40	\$ 32,000
12.	Remove Existing Culvert	75 LF	\$ 35	\$ 2,625
13.	Remove Asphalt Pavement	200 SY	\$ 5	\$ 1,000
14.	Crushed Surfacing Base Course	40 TN	\$ 35	\$ 1,400
15.	Light Loose Riprap	70 TN	\$ 80	\$ 5,600
16.	Streambed Gravel	170 TN	\$ 50	\$ 8,500
17.	HMA, CL 1/2-in PG 64-22	50 TN	\$ 145	\$ 7,250
18.	50-ft Single Span Bridge	1 LS	\$ 260,000	\$ 260,000
19.	Concrete Footings (class 4000)	80 CY	\$ 750	\$ 60,000
20.	Large Woody Debris	5 EA	\$ 2,700	\$ 13,500
21.	Surface Restoration (seeding, fertilizing, planting, etc)	190 SY	\$ 7	\$ 1,330
22.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 523,000
	Construction Contingencies (20%)			\$ 105,000
	Sales Tax (9.1%)			\$ 48,000
	Total Construction Cost			\$ 676,000
	Design, Engineering & Construction Management (25%)			\$ 169,000
	Permitting (25%)			\$ 169,000
	Easements (Temporary & Permanent)	1000 SF	\$ 1	\$ 1,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	2 EA	\$ 1,000	\$ 2,000
TOTAL PROJECT COST				\$ 1,017,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC12: Culvert Removal and Bridge Installation at 103rd Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 46,000	\$ 46,000
3.	Project Temporary Traffic Control	1	LS	\$ 9,000	\$ 9,000
4.	Locate Existing Utilities	1	LS	\$ 2,000	\$ 2,000
5.	Survey	1	LS	\$ 5,000	\$ 5,000
6.	Utility Relocation	1	LS	\$ 10,000	\$ 10,000
7.	Temporary Erosion Control	1	LS	\$ 10,000	\$ 10,000
8.	Dewatering	1	LS	\$ 15,000	\$ 15,000
9.	Clearing and Grubbing	0.10	AC	\$ 15,000	\$ 1,500
10.	Temporary Bypass	1	LS	\$ 15,000	\$ 15,000
11.	Excavation Incl. Haul	700	CY	\$ 40	\$ 28,000
12.	Remove Existing Pipe	35	LF	\$ 30	\$ 1,050
13.	Remove Asphalt Pavement	160	SY	\$ 5	\$ 800
14.	Crushed Surfacing Base Course	40	TN	\$ 35	\$ 1,400
15.	Light Loose Riprap	70	TN	\$ 80	\$ 5,600
16.	Streambed Gravel	170	TN	\$ 50	\$ 8,500
17.	HMA, CL 1/2-in PG 64-22	40	TN	\$ 145	\$ 5,800
18.	50-ft Single Span Bridge	1	LS	\$ 260,000	\$ 260,000
19.	Concrete Footings (class 4000)	80	CY	\$ 750	\$ 60,000
20.	Large Woody Debris	5	EA	\$ 2,700	\$ 13,500
21.	Surface Restoration (seeding, fertilizing, planting, etc)	190	SY	\$ 7	\$ 1,330
22.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 503,000
	Construction Contingencies (20%)				\$ 101,000
	Sales Tax (9.1%)				\$ 46,000
	Total Construction Cost				\$ 650,000
	Design, Engineering & Construction Management (25%)				\$ 163,000
	Permitting (25%)				\$ 163,000
	Easements (Temporary & Permanent)	1000	SF	\$ 1	\$ 1,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	3	EA	\$ 1,000	\$ 3,000
TOTAL PROJECT COST					\$ 980,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
QC13: Culvert Removal and Bridge Installation along Quilceda Creek at State Avenue
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 328,000	\$ 328,000
3.	Project Temporary Traffic Control	1 LS	\$ 157,000	\$ 157,000
4.	Locate Existing Utilities	1 LS	\$ 5,000	\$ 5,000
5.	Survey	1 LS	\$ 54,000	\$ 54,000
6.	Utility Relocation	1 LS	\$ 25,000	\$ 25,000
7.	Temporary Erosion Control	1 LS	\$ 100,000	\$ 100,000
8.	Dewatering	1 LS	\$ 200,000	\$ 200,000
9.	Clearing and Grubbing	0.25 AC	\$ 15,000	\$ 3,750
10.	Temporary Bypass	1 LS	\$ 50,000	\$ 50,000
11.	Excavation Incl. Haul	22600 CY	\$ 40	\$ 904,000
12.	Remove Existing Pipe	180 LF	\$ 30	\$ 5,400
13.	Remove Asphalt Pavement	890 SY	\$ 5	\$ 4,450
14.	Crushed Surfacing Base Course	270 TN	\$ 35	\$ 9,450
15.	Light Loose Riprap	140 TN	\$ 80	\$ 11,200
16.	Streambed Gravel	300 TN	\$ 50	\$ 15,000
17.	HMA, CL 1/2-in PG 64-22	210 TN	\$ 145	\$ 30,450
18.	180-ft Single Span Bridge	1 LS	\$ 1,500,000	\$ 1,500,000
19.	Concrete Footings (class 4000)	170 CY	\$ 750	\$ 127,500
20.	Large Woody Debris	20 EA	\$ 2,700	\$ 54,000
21.	Surface Restoration (seeding, fertilizing, planting, etc)	1600 SY	\$ 7	\$ 11,200
22.	Project Documentation	1 LS	\$ 10,000	\$ 10,000
Subtotal				\$ 3,607,000
Construction Contingencies (20%)				\$ 722,000
Sales Tax (9.1%)				\$ 329,000
Total Construction Cost				\$ 4,658,000
Design, Engineering & Construction Management (25%)				\$ 1,165,000
Permitting (20%)				\$ 932,000
Easements (Temporary & Permanent)				0 SF \$ 1 \$ -
Fixed costs for Easements (Negotiations, Agent, Survey, etc.)				0 EA \$ 1,000 \$ -
TOTAL PROJECT COST				\$ 6,755,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
AC1: Storm Pipe Replacement at 95th Street NE and 67th Avenue NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 9,000	\$ 9,000
3.	Project Temporary Traffic Control	1 LS	\$ 8,000	\$ 8,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Relocate Existing Utilities	1 LS	\$ 5,000	\$ 5,000
7.	Temporary Erosion Control	1 LS	\$ 3,600	\$ 3,600
8.	Dewatering	1 LS	\$ 3,600	\$ 3,600
9.	Trench Excavation Safety Systems	227 LF	\$ 5	\$ 1,135
10.	Excavation Incl. Haul	300 CY	\$ 40	\$ 12,000
11.	Remove Existing Pipe	227 LF	\$ 30	\$ 6,810
12.	Sawcutting	464 LF	\$ 3	\$ 1,392
13.	Remove Asphalt Pavement	160 SY	\$ 5	\$ 800
14.	Crushed Surfacing Base Course	40 TN	\$ 35	\$ 1,400
15.	Gravel Borrow	10 TN	\$ 26	\$ 260
16.	Asphalt Treated Base	40 TN	\$ 100	\$ 4,000
17.	HMA, CL 1/2-in PG 64-22	28 TN	\$ 145	\$ 4,060
18.	18-inch Storm Pipe incl. Bedding	227 LF	\$ 60	\$ 13,620
19.	48-inch Type II Storm Manhole	1 EA	\$ 4,000	\$ 4,000
20.	Connect to Drainage Structure	2 EA	\$ 700	\$ 1,400
21.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 91,000
	Construction Contingencies (20%)			\$ 18,200
	Sales Tax (9.1%)			\$ 9,000
	Total Construction Cost			\$ 118,200
	Design, Engineering & Construction Management (25%)			\$ 30,000
	Permitting (10%)			\$ 12,000
	Easements (Temporary & Permanent)	0 AC	\$ 40,000	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	0 EA	\$ 1,000	\$ -
TOTAL PROJECT COST				\$ 161,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
AC2: Culvert Replacement and Erosion Control Measures at 88th Street NE
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 42,000	\$ 42,000
3.	Project Temporary Traffic Control	1	LS	\$ 32,000	\$ 32,000
4.	Temporary Erosion Control	1	LS	\$ 15,000	\$ 15,000
5.	Dewatering	1	LS	\$ 15,000	\$ 15,000
6.	Temporary Bypass	1	LS	\$ 30,000	\$ 30,000
7.	Roadway Excavation	640	CY	\$ 25	\$ 16,000
8.	Remove Existing Pipe	100	LF	\$ 30	\$ 3,000
9.	Sawcutting	60	LF	\$ 3	\$ 180
10.	Remove Asphalt Pavement	240	SY	\$ 5	\$ 1,200
11.	Crushed Surfacing Base Course	80	TN	\$ 35	\$ 2,800
12.	Gravel Borrow	150	TN	\$ 26	\$ 3,900
13.	Streambed Gravel	170	TN	\$ 50	\$ 8,500
14.	HMA, CL 1/2-in PG 64-22	60	TN	\$ 145	\$ 8,700
15.	25-ft Span Reinforced Concrete Box Culvert	80	LF	\$ 3,500	\$ 280,000
16.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 462,000
	Construction Contingencies (20%)				\$ 93,000
	Sales Tax (9.1%)				\$ 43,000
	Total Construction Cost				\$ 598,000
	Design, Engineering & Construction Management (25%)				\$ 150,000
	Permitting (25%)				\$ 150,000
	Easements (Temporary & Permanent)	0	SF	\$ 1	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	0	EA	\$ 1,000	\$ -
TOTAL PROJECT COST					\$ 898,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
AC3: Storm Pipe Replacement at 61st Street NE Cul-de-sac
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 17,000	\$ 17,000
3.	Project Temporary Traffic Control	1 LS	\$ 4,000	\$ 4,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1 LS	\$ 5,000	\$ 5,000
7.	Dewatering	1 LS	\$ 15,000	\$ 15,000
8.	Trench Excavation Safety Systems	680 LF	\$ 5	\$ 3,400
9.	Excavation Incl. Haul	790 CY	\$ 40	\$ 31,600
10.	Remove Existing Pipe	680 LF	\$ 30	\$ 20,400
11.	Sawcutting	1370 LF	\$ 3	\$ 4,110
12.	Remove Asphalt Pavement	460 SY	\$ 5	\$ 2,300
13.	Crushed Surfacing Base Course	100 TN	\$ 35	\$ 3,500
14.	Gravel Borrow	10 TN	\$ 26	\$ 260
15.	HMA, CL 1/2-in PG 64-22	90 TN	\$ 145	\$ 13,050
16.	12-inch Storm Pipe incl. Bedding	160 LF	\$ 45	\$ 7,200
17.	15-inch Storm Pipe incl. Bedding	520 LF	\$ 50	\$ 26,000
18.	48-inch Type II Storm Manhole	5 EA	\$ 4,000	\$ 20,000
19.	Connect to Drainage Structure	3 EA	\$ 700	\$ 2,100
20.	Project Documentation	1 LS	\$ 2,000	\$ 2,000
	Subtotal			\$ 185,000
	Construction Contingencies (20%)			\$ 37,000
	Sales Tax (9.1%)			\$ 17,000
	Total Construction Cost			\$ 239,000
	Design, Engineering & Construction Management (25%)			\$ 60,000
	Permitting (10%)			\$ 24,000
	Easements (Temporary & Permanent)	0 AC	\$ 40,000	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	0 EA	\$ 1,000	\$ --
TOTAL PROJECT COST				\$ 323,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
AC4: Storm Pipe Replacement at 60th Place NE and surrounding area
September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 34,000	\$ 34,000
3.	Project Temporary Traffic Control	1 LS	\$ 17,000	\$ 17,000
4.	Locate Existing Utilities	1 LS	\$ 5,000	\$ 5,000
5.	Survey	1 LS	\$ 10,000	\$ 10,000
6.	Utility Coordination	1 LS	\$ 10,000	\$ 10,000
7.	Temporary Erosion Control	1 LS	\$ 10,000	\$ 10,000
8.	Dewatering	1 LS	\$ 15,000	\$ 15,000
9.	Trench Excavation Safety Systems	1230 LF	\$ 5	\$ 6,150
10.	Excavation Incl. Haul	1500 CY	\$ 40	\$ 60,000
11.	Remove Existing Pipe	1230 LF	\$ 30	\$ 36,900
12.	Sawcutting	2470 LF	\$ 3	\$ 7,410
13.	Remove Asphalt Pavement	760 SY	\$ 5	\$ 3,800
14.	Crushed Surfacing Base Course	160 TN	\$ 35	\$ 5,600
15.	Gravel Borrow	30 TN	\$ 26	\$ 780
16.	HMA, CL 1/2-in PG 64-22	140 TN	\$ 145	\$ 20,300
17.	15-inch Storm Pipe incl. Bedding	780 LF	\$ 50	\$ 39,000
18.	18-inch Storm Pipe incl. Bedding	450 LF	\$ 60	\$ 27,000
19.	48-inch Type II Storm Manhole	13 EA	\$ 4,000	\$ 52,000
20.	Connect to Drainage Structure	10 EA	\$ 700	\$ 7,000.00
21.	Surface Restoration (seeding, fertilizing, planting, etc)	70 SY	\$ 7	\$ 490
22.	Project Documentation	1 LS	\$ 5,000	\$ 5,000
	Subtotal			\$ 374,000
	Construction Contingencies (20%)			\$ 75,000
	Sales Tax (9.1%)			\$ 34,100
	Total Construction Cost			\$ 483,100
	Design, Engineering & Construction Management (25%)			\$ 121,000
	Permitting (10%)			\$ 49,000
	Easements (Temporary & Permanent)	0 AC	\$ 40,000	\$ -
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	0 EA	\$ 1,000	\$ -
TOTAL PROJECT COST				\$ 654,000

**CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE**

ES2: Water Quality Treatment Facility at Downtown Marina Outfall

September 20, 2016

G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT PRICE	AMOUNT
1.	SPCC Plan	1 LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1 LS	\$ 445,000	\$ 445,000
3.	Project Temporary Traffic Control	1 LS	\$ 5,000	\$ 5,000
4.	Locate Existing Utilities	1 LS	\$ 2,000	\$ 2,000
5.	Survey	1 LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1 LS	\$ 20,000	\$ 20,000
7.	Dewatering	1 LS	\$ 75,000	\$ 75,000
8.	Clearing and Grubbing	0.28 AC	\$ 15,000	\$ 4,132
9.	Excavation Incl. Haul	1,800 CY	\$ 10	\$ 18,000
10.	Inlet and Outlet Controls	2 LS	\$ 50,000	\$ 100,000
11.	Treatment Facility	12,000 SF	\$ 350	\$ 4,200,000
12.	Surface Restoration (seeding, fertilizing, planting, etc)	1,344 SY	\$ 7	\$ 9,411
13.	Project Documentation	1 LS	\$ 5,000	\$ 5,000
	Subtotal			\$ 4,890,000
	Construction Contingencies (20%)			\$ 978,000
	Sales Tax (9.1%)			\$ 445,000
	Total Construction Cost			\$ 6,313,000
	Design, Engineering & Construction Management(25%)			\$ 1,579,000
	Permitting (5%)			\$ 316,000
TOTAL PROJECT COST				\$ 8,208,000

CITY OF MARYSVILLE
ENGINEER'S COST ESTIMATE
KC1: Culvert Replacement along King Creek at Soper Hill Road

September 1, 2016
G&O # 15550

NO.	DESCRIPTION	QUANTITY	UNIT	PRICE	AMOUNT
1.	SPCC Plan	1	LS	\$ 1,000	\$ 1,000
2.	Mobilization, Cleanup and Demobilization	1	LS	\$ 77,000	\$ 77,000
3.	Project Temporary Traffic Control	1	LS	\$ 24,000	\$ 24,000
4.	Locate Existing Utilities	1	LS	\$ 3,000	\$ 3,000
5.	Survey	1	LS	\$ 5,000	\$ 5,000
6.	Temporary Erosion Control	1	LS	\$ 10,000	\$ 10,000
7.	Dewatering	1	LS	\$ 15,000	\$ 15,000
8.	Temporary Bypass	1	LS	\$ 35,000	\$ 35,000
9.	Excavation Incl. Haul	5220	CY	\$ 40	\$ 208,800
10.	Remove Existing Pipe	100	LF	\$ 30	\$ 3,000
11.	Sawcutting	44	LF	\$ 3	\$ 132
12.	Remove Asphalt Pavement	200	SY	\$ 5	\$ 1,000
13.	Crushed Surfacing Base Course	40	TN	\$ 35	\$ 1,400
14.	Gravel Borrow	240	TN	\$ 26	\$ 6,240
15.	Streambed Gravel	410	TN	\$ 50	\$ 20,500
16.	Quarry Spalls	300	TN	\$ 60	\$ 18,000
17.	Stream Boulders	200	EA	\$ 400	\$ 80,000
18.	HMA, CL 1/2-in PG 64-22	47	TN	\$ 145	\$ 6,800
19.	Guardrail	160	LF	\$ 30	\$ 4,800
20.	17-ft Span Reinforced Concrete Box Culvert	160	LF	\$ 2,000	\$ 320,000
21.	Surface Restoration (seeding, fertilizing, planting, etc)	230	SY	\$ 7	\$ 1,610
22.	Project Documentation	1	LS	\$ 2,000	\$ 2,000
	Subtotal				\$ 845,000
	Construction Contingencies (20%)				\$ 169,000
	Sales Tax (9.1%)				\$ 77,000
	Total Construction Cost				\$ 1,091,000
	Design, Engineering & Construction Management (25%)				\$ 273,000
	Permitting (20%)				\$ 219,000
	Easements (Temporary & Permanent)	5000	SF	\$ 1	\$ 5,000
	Fixed costs for Easements (Negotiations, Agent, Survey, etc.)	2	EA	\$ 1,000	\$ 2,000
TOTAL PROJECT COST					\$ 1,590,000